



## IP68 Outdoor Full Color Led Screen High Illumination LED Panel Screen

Our Product Introduction


### Basic Information

- Place of Origin: Shenzhen China
- Brand Name: SOL COLUR
- Certification: SO9001 3C CE FCC IP65 IP68 ISO14001 ROHS
- Model Number: P6
- Minimum Order Quantity: 1 Square Meters
- Price: USD 550-600 Square Meters
- Packaging Details: Wooden box flight case,
- Delivery Time: 10 days after received deposit
- Payment Terms: D/A, L/C, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 Square Meter/Square Meters per Month




### Product Specification

- Product Name: P6 Outdoor Digital Advertising Led Display
- Color: Full Color
- Application: Illumination
- Certificate: SO9001 3C CE FCC IP65 IP68 ISO14001 ROHS
- Warranty: 3 Years
- Chip: Taiwan MacroBlock
- Highlight: **Outdoor Full Color Led screen High Illumination , High Illumination LED Panel Screen, IP68 Outdoor Full Color Led Screen**



### More Images



for more products please visit us on [sol-colur.com](http://sol-colur.com)

## Product Description

Outdoor Digital LED Advertising Display Board , High Illumination LED Panel Screen

P1.25/P1.388/P1.5625/P1.667/P1.875/P1.923/P2/P2.5/P3/P3.91/P4.81

P4/P5/P6/P7.62/P8/P10/P12/P16

### P6 outdoor digital advertising led display module

#### Specifications of P6mm outdoor digital advertising

SS6outdoor full-color technology parameters

Unit Module	Item	Parameter
	Model Number	SF-SS6-8-A
	Module size	192mm*192mm
	Pixel pitch	6mm
	Pixels Density	27777Pixel/m2
	Pixel configuration	1R1G1B
	Package mode	SMD3535
	Pixel resolution	32dots(W)*32dots(H)
	Max Power	25W
	Module thickness	17.5mm
	Weight	0.38kg
	Drive type	Constant drive
	Scan mode	1/8
	Port type	HUB75-B
Brightness of white balance	≥6000 6500cd/m2	
Module pictures		
Cabinet	Dimension	960mm*960mm*100 mm
	Monomer Module Number	25pcs
	Power supply	5V/40A*5pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	96mm*96mm
	Best viewing distance	6M 30M
	Best viewing angle	120°(W)110°(H)
	Temperature	storage:-35℃ +85℃ working:-20℃ +50℃
	Relative humidity	10%-95%
	Thickness	117.5mm
Power	Working voltage	AC220V±10%
	Average Power consumption	400W/
	Max.Power consumption	≤1200W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1200HZ
	Grey scale/colors	4096,16.7M 4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

## Project Cases

□

□□□

### Company information

SHENZHEN SOL COLUR DISPLAY CO.,LTD. was established in December 2012,Is a leading LED display applications products and solutions provider,Specialized in LED research and development, manufacturing. Sales and servic,Dedicated to providing high-quality, high-performance LED applications and solutions for professional channel customers and end-users at home and abroad.

Our products have been widely used both at home and abroad. Since its foundation, we have become one of the best LED product and solution providers in the country through our unremitting efforts and have won the industry's highest recognition

The development of the company so far, the sales outlets throughout the country, the export products exported to more than 10 countries and regions, 3C, FCC, CE, IFA, IP65, IP68, IS9001, ROHS.AAA and other qualifications, product testing reports, patent certificate

**SOL COLUR** SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen