



P4.81 Outdoor LED Display Cabinet High Resolution Die Casting Aluminum For Airports

Our Product Introduction


Basic Information

- Place of Origin: Shenzhen China
- Brand Name: SOL COLUR
- Certification: SO9001 3C CE FCC IP65 IP68 ISO14001 ROHS
- Model Number: P4.81
- Minimum Order Quantity: 1 Square Meters
- Price: USD 950-1000 Square Meters
- Packaging Details: Wooden box flight case,
- Delivery Time: 10 days after received deposit
- Payment Terms: D/A, L/C, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 Square Meter/Square Meters per Month




Product Specification

- Product Name: P4.81 Outdoor Rental Led Display Screen
- Color: Full Color
- Application: Illumination
- Certificate: SO9001 3C CE FCC IP65 IP68 ISO14001 ROHS
- Warranty: 3 Years
- Chip: Taiwan MacroBlock



More Images



for more products please visit us on sol-colur.com

Product Description

China Factory P4.81 outdoor led display screen/ outdoor led display cabinets /rental display screen

We produce indoor outdoor and rental led module and led display

P1.25/P1.388/P1.5625/P1.667/P1.875/P1.923/P2/P2.5/P3/P3.91/P4.81

P4/P5/P6/P7.62/P8/P10/P12/P16

Specifications of P4.81mm outdoor rental

Unit Module	Item	Parameter
	Model Number	HX-P4.81-13S
	Module size	250mm*250mm
	Pixel pitch	4.81mm
	Pixels Density	43264Pixel
	Pixel configuration	1R1G1B
	Package mode	SMD2727
	Pixel resolution	52dots(W)*52 dots (H)
	Max Power	35W
	Weight	0.65kg
	Drive type	Constant drive
	Scan mode	1/13 1/13scan
	Port type	HUB75-A
	Brightness of white balance	≥4500cd/m2

Cabinet	Dimension	500mm*500mm
	Monomer Module Number	4pcs
	Power supply	5V/40A*1pcs
	Thermal discharge	fan 1pcs
	Pixel per cabinet	104*104
	Best viewing distance	5M 20M
	Best viewing angle	160°(W) 120°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
Power	Thickness	65mm
	Working voltage	AC110 220V±10%
	Average Power consumption	<320W/
	Max.Power consumption	<800W/
Control system	Current	<20mA(single LED)
	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	>1920HZ
	Grey scale/colors	16384 16.7M 16384gray level/16.7M colors
	MTBF	>9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

P4.81outdoor rental led display module

Project Cases

Company information

SHENZHEN SOL COLUR DISPLAY CO.,LTD. was established in December 2012,Is a leading LED display applications products and solutions provider,Specialized in LED research and development, manufacturing. Sales and servic,Dedicated to providing high-quality, high-performance LED applications and solutions for professional channel customers and end-users at home and abroad.

Our products have been widely used both at home and abroad. Since its foundation, we have become one of the best LED product and solution providers in the country through our unremitting efforts and have won the industry's highest recognition

The development of the company so far, the sales outlets throughout the country, the export products exported to more than 10 countries and regions, 3C, FCC, CE,IFA, IP65, IP68, IS9001, ROHS.AAA and other qualifications, product testing reports, patent certificate



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen