



Adjustable Brightness Outdoor Fixed LED Display For Media Advertising Weather Proof

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: CE,3C,FCC
- Model Number: P10
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Color: Full Color
- Brightness: 6500
- Warranty: 2 Years
- Certificate: CE
- Usage: Outdoor
- Place Of Origin: Shenzhen China
- Highlight: **Adjustable Brightness Outdoor Fixed LED Display**
, Weather proof Outdoor Fixed LED Display ,
Weather proof Outdoor Advertising Led Display



More Images



for more products please visit us on sol-colur.com

Product Description

Adjustable Brightness Outdoor SMD LED Display Low Power Consumption For Media Advertising

Specifications

1. p10 outdoor full color led display
2. High refresh rate:>600hz
3. High brightness:>8500cd/2
4. 2 years warranty

Features:

- 1) With good lightening accordance and no mosaic
- 2) Led advertising board can play different formats of image files, flash, WAV/MIDI, video signal from TV, video signal from video and other equipment
- 3) Different video frequency can be changed freely at the same time, and the image can be enlarged and reduced
- 4) High brightness, and can be adjustable, meets the need of changing requirement of customer in environment
- 5) Uses real pixels rather than virtual pixels, better viewing eff

Parameter

No	Item	Parameter
1	Pixel Pitch	10mm
2	Pixel Configuration	1R1G1B / R:G:B=3:6:1
3	LED Lamp	Full color
4	Density	10000dot/m ²
5	Module Size	320*160mm
6	Module Pixel	32*16=512dot
7	Module Thickness	17mm
8	Module Weight	395g
9	Module Power	≤63W
10	Drive Valtage	DC5V
11	Module Electric Current	11-12.5A
12	PortType	HUB-75D/B
No	Item	Parameter
1	Standard Caninet Size	960mm*960mm*130mm
2	Cabinet Weight	9.85KGS
3	Brightness/Adjustment	≥7800cd/m ² , Level 16- Automatic / Level 100-Manual operation
4	View Angle	≥120°(Vertical),≥120°(Horizontal)
5	Best View Distance	10-100m
6	Grey Scale	Within 65536 Step
7	Frame Frequency	≥60Hz
8	Refresh Rate	≥1560Hz
9	Signal Input Source	Composite, S-video, Component, VGA, DVI, HDMI, SDI, HD-SDI
10	Scan Mode	1/2 1/4
11	Drive IC	5020
12	Module Qty / M ²	19.5
13	Display Color Qty	16777216
14	Continuous Working Time	>24(Hrs)
15	Screen Lifespan	>100,000(Hrs)
16	MTBF	>5000(Hrs)
17	Max. power consumption	1250W/
18	Ave. power consumption	420W/
19	Out of control pixel rate	≥3/10,000(discrete distribution)
20	Control Distance	100M(Ethernet) 500M(Multi-fiber) 10KM(Sigle-fiber)
21	Flatness	Screen Surface≤0.5mm,Pixel Pitch≤0.3mm
22	Operation Temperature	-10°C +50°C
23	Working Humidity	10% 98%RH
24	Storage Temperature	-40°C +85°C
25	Software Connection	Standard Computer Connection,Compatible With Windows,Unix,Novell

26	protection system	Overtemperature/overload/power/image compensation/nonlinear correction
27	Working Valtage	200~240 V
28	Dielectric Strength	50HZ/1500V(AC RMS)/1min
29	Temperature Rise	Metal≤40K,Insulation≤65K , After Heat Balance
30	IP Grade	IP65
31	Computer display mode	1024*768
33	Media Player	LED Pressional Media Player

Project Cases



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen