



SMD P5.95 Creative Stage LED Display IP65 High Resolution Outdoor

Our Product Introduction

for more products please visit us on sol-colur.com

Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: CE,3C,FCC ,ROSH
- Model Number: P5.95 Outdoor
- Minimum Order Quantity: 1 Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Color: Full Color
- Brightness: 5100
- Driver IC: MBI 5124
- Certificate: CE
- Usage: Outdoor
- Place Of Origin: Shenzhen China
- Highlight: Stage LED Display IP65,
P5.95 Stage LED Display ,
P5.95 led stage screen



More Images



Product Description

Hd Video SMD P5.95 LED Screen Panel High Resolution Outdoor Led Tv Display Screen

Product Quick Details:

- 1, Pixel pitch: 5.95mm
- 2, Protection level: IP65
- 3, Silent design without fans.

Product Features:

- 1, IC MBI5124 is used, high refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.
- 2, Cabinet size is 500*1000mm, thickness 75cm, and weight is only 14.2kg/pc, very light and slim, makes much easier for transporting, installation and movement, could save your cost and time.
- 3, Die-cast aluminum with CNC is finished, the dimension tolerance of less than 0.01mm, and module shaping one time, the machining accuracy of + 0.01mm, easy to realize seamless splicing.
- 4, Alignment hole and location pin design for installation could achieve extreme precision between cabinets, besides module shaping one time, get seamless splicing and assemble easier.
- 5, Cabinet size is 500*1000mm, thickness 75cm, and weight is only 14.2kg/pc, very light and slim, makes much easier for transporting, installation and movement, could save your cost and time.
- 6, Protection level IP65, is full waterproof, dustproof, anti-corrosion and anti-ultraviolet, enable themselves to work in all weather conditions to guarantee durability, reliability and steady.
- 7, High brightness ensures the spectators far from the screen can still enjoy what is shown, even under direct sunlight.

Parameter

Item Name	P5.95 outdoor rental LED display screen
Item No.	P5.95
Pixel Pitch	5.95mm
Pixel Configuration	1R1G1B (3 in 1)
LED Encapsulation	White SMD3535
Pixel Density	28224pixels/m ²
Driving Method	1/7 scan
Refresh Frequency	≥1920Hz
Driver IC	Special constant current IC with high refresh rate & high gray scale
Grey Scale	14Bit (depending on the system and IC configuration)
Cabinet size	500 x 500mm
white balance brightness	≥5000cd/ m ²
Color Temperature	8000K±500(adjustable)
Viewing Angle	Horizontal 130° Vertical 100°
Optimal Viewing Distance	>6m
Working Voltage	AC 220V/110V±10%
Module voltage	DC4.2V
Max Power Consumption	200W/Pcs
Avg.Power Consumption	100W/pcs
Lifetime	100000 hours
Operating Temperature	-10℃ ~ 65℃

Product Show



SOL COLUR  **SHENZHEN SOL COLUR DISPLAY CO.,LTD**

 +86 13751136904

 chenhao@sol-colour.com

 sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen