



Dustproof IP43 Stage Background Led Screen , Events Outdoor Video Screen Rental

Our Product Introduction

for more products please visit us on sol-colur.com

Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: ROHS,FCC,IP65,3C,CE
- Model Number: P3.91 Indoor
- Minimum Order Quantity: 1 Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month




Product Specification

- Package Mode: SMD Nationstar
- Scan Mode: 16S
- Warranty: 3 Years
- Power Supply: Meanwell
- Uasge: Indoor
- Module Size: 250mm*250mm



More Images



Product Description

P3.91 Indoor Rental LED Display Easy Installation indoor full color video screen / for stage

Description

- * Die-casting aluminum /extrusion aluminum secure and nice in constitution.
- * No fans, mute when operation.
- * Dustproof, IP43.
- * High refresh rate and high gray depth.
- * Completely black LED with high contrast.
- * Standard cabinet size is 500mm x 500mm and 480x480mm.
- * Large viewing angle, the panel viewing angle is up to 140, the vertical angle could reach 140, the image won't be out of shape and color cast between the rang.
- * Exactly connected and easy to install and dismount

Parameter

*Specifications of the module		
Technical parameters	UNIT	Parameters values
Pixel pitch	MM	3.91
Panel size	MM	L250*H250*T13
Physical density	/M ²	65410
Pixel configuration	R/G/B	1,1,1
Driving method		Constant current 1/13scan
LED Encapsulation	SMD	2121
Display resolution	DOTS	64X64=4096
Module weight	KG	0.32
Module port		HUB75-B
Module working voltage	VDC	5
Module consumption	W	30
*Specifications of LED cabinet		
Cabinet size	mm	500*500 / 500*1000
Cabinet weight	5kg	5.5 / 10.8
Cabinet resolution	dots	128*128 / 128*256
Viewing angle	Deg.	140°
Option distance	M	3-50
Driving device		16016
Every square metre module	PCS	16
Maximum power	W/ M ²	1000
Frame Frequency	HZ/S	≥60
Refresh frequency	HZ/S	≥600
Equilibrium brightness	CD/ M ²	≥1500
Working environment temperature	°C	-10~60
Working environment humidity	RH	10% 70%
Display working voltage	VAC	AC46 54HZ,220V±15%/110V±15%
Colour temperature		8500K-11500K
Gray scale/color		≥16.7M color
Input signal		RF S-Video RGB etc
Control system		PCTV nonlinearity card,DVI display card,Linsn control system
Mean free error time	HOURS	5000
Life	HOURS	100000
Lamp failure frequency		0.0001
Antijam		IEC801
Safety		GB4793
Resist the electricity		1500V last 1min No breakdown
Steel box weight	KG/ M ²	40(standard steel box)
Earth leakage current	mA	
IP rating		The back IP40,The front IP50
Steel box size	mm	L768Xh768x80

PH3.91 Features

1. Super Light and Thin
14KG/panel with a depth of 80mm which is half of the depth of traditional LED screen,saving space and transportation cost.

2. High Refresh Rate
Refresh Rate \geq 2000, offering impressive visual effect.

Application of P3.91mm

1. Conference room, Concert, Grand Ballroom, Studio, Bar, Stage, Theater, Meeting Room, Banquet Hall and etc.

2. High Refresh Rate
Refresh Rate \geq 2000, offering impressive visual effect.

3. Noiseless
Free of fans and air conditions, excluding noise and reducing power consumption.

4. Fine and Smooth Picture
Drive IC of high refresh rate and high grey scale to ensure stable picture and better visual effect of the screen. The latest horizontal-blanking circuit applied to completely eliminate phenomenon of blanking and smear.

P3.91 System Connection Diagram



Product Show



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen