# Wigh Potycols Rate 2 01 pers Curved I ED Display Covers Coombase

# High Refresh Rate 3.91mm Curved LED Display Screen Seamless Splicing

## **Basic Information**

Place of Origin: SHENZHEN

• Brand Name: SC

Certification: CE.3C,FCC ,ROSH
 Model Number: P3.91 indoor Curved
 Minimum Order Quantity: 1 Square Meters / 1 Piece

• Price: Negotiable

Packaging Details: Wooden box,Flight Case
 Delivery Time: 10 days after received deposit
 Payment Terms: L/C, D/A, D/P, T/T, Western Union
 Supply Ability: 5000 Square Meter/Square Meters per

Month



# **Product Specification**

Color: Full Color
Brightness: 1500
Warranty: 2Years
Certificate: CE,FCC,3C
Uasge: Indoor

Place Of Origin:
 Shenzhen China

• Highlight: 3.91mm Curved LED Display,

Curved LED Screen Seamless Splicing, Curved LED Display Seamless Splicing



# More Images





### **Product Description**

High Refresh Rate Curved LED Display Screen Die - Cast Aluminum Cabinet 500 X 1000mm

#### **Product Quick Details:**

- 1, Die-cast aluminum cabinet 500x1000mm and 500X500mm
- 2, Wide viewing angle
- 3, Seamless splicing

#### **Product Features:**

- 1, There are three handles for lifting cabinets, aviation plug and fast lock on each side is equipped, makes very convenient and comfortable for fast installation by one person without tools, besides guarantee seamless installation and keep smoothly
- 2, Die-cast aluminum with CNC is finished, the dimension tolerance of less than 0.01mm, and module shaping one time, the machining accuracy of + 0.01mm, easy to realize seamless splicing.
- 3, Use special heat dissipation, quiet working without fans.
- 4, Pixel density is 65746 dots per square meter, high resolution brings HD visual effect.
- 5, SMD guarantee super wide viewing angle, higher flatness and better performance, offers you clear and natural images in all directions. high quality full black leds, together with black mask, achieves clear and crystal picture.
- 6, Alignment hole and location pin design for installation could achieve extreme precision between cabinets, seam splicing is less than 0.05mm.
- 7, High refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.

#### **Parameter**

Unit Module	Item	Parameter
	Model Number	HX-P3.91-16S
	Module size	250mm*250mm
	Pixel pitch	3.91mm
	Pixels Density	65536 Pixels/m2
	Pixel configuration	1R1G1B
	LED Package mode	SMD1921
	Pixel resolution	64dots(W)*64 dots(H)
	Max Power	38W
	Module weight	0.7kg
	Drive type	Constant drive
	Scan mode	1/16Scan 1/16scan
	Port type	HUB75-A
	Brightness of white balance	≥4800cd/m2

#### P3.91 System Connection diagram



**Product Show** 





# SULCUL YUK SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen