



High Efficiency Led Big Screen 6500Nits Brightness XP/WIN7 Control System

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: ISO9001,FCC,IP65,3C ,ROSH
- Model Number: P8 Outdoor
- Minimum Order Quantity: 1 Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month




Product Specification

- Brightness: 6500Nits
- Scan Mode: 8S
- Warranty: 2 Years
- Driver IC: MBI 5124
- Uasge: Outdoor
- Place Of Origin: Shenzhen China
- Highlight: **Led Big Screen 6500Nits ,
High Efficiency Led Big Screen ,
6500Nits large led display**



More Images



for more products please visit us on sol-colur.com

Product Description

High Efficiency LED Screen Panels , 6500Nits Brightness Led Big Screen XP/WIN7 Control System

Product Features

- 1, High refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.
- 2, High brightness ensures the spectators far from the screen can still enjoy what is shown, even under direct sunlight
- 3, SMD2727 technology could guarantee higher flatness and better performance.
- 4, Using high brightness and high efficiency of LED lamps;

Applications :

Our full color LED display are widely used in commercial advertising, entertainment industry, financial industry, communications, power sector, traffic, stadium, plaza, school, airport, bus station etc., for advertising and displaying messages.

Shipping :

We will recommend the suitable shipping and delivery method as to goods condition.

- 1 . By Ocean shipping
- 2 . By Air transport
- 3 . By Express such as DHL / FedEx / UPS / TNT

Parameter

Unit Module	Item	Parameter
	Model Number	SF-SS8-4-A
	Module size	256mm*128mm
	Pixel pitch	8mm
	Pixels Density	15625Pixels /m2
	Pixel configuration	1R1G1B
	LED Package mode	NationstarSMD3535
	Pixel resolution	32dots(W)*16dots(H)
	Max Power	25W
	Module thickness	22mm
	Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6000 6500cd/m2
Module pictures		
LED Cabinet	Dimension	1024mm*768mm*100 mm
	Monomer Module Number	24pcs
	Power supply	5V/40A*4 pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	128mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	330W/
	Max.Power consumption	≤1100W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC

	Refresh frequency	≥1200HZ
	Grey scale/colors	4096,16.7MColor 4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

Product Cases



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904 chenhao@sol-colour.com sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen