High Refresh Rate Indoor Led Screen Hire, P4.81 3in1 Window Large Led **Video Screens**

Basic Information

. Place of Origin: SHENZHEN

SC . Brand Name:

ROSH,3C,FCC,IP65,SO9001 · Certification:

Model Number: P4.81 indoor • Minimum Order Quantity: 1 Square Meters • Price: Negotiable

Wooden box, Flight Case Packaging Details: • Delivery Time: 10 days after received deposit Payment Terms: L/C, D/A, D/P, T/T, Western Union . Supply Ability: 5000 Square Meter/Square Meters per

Month



Product Specification

• Usage: Indoor . Brightness: 1500 Full Color · Color: Certificate: CE,3C,FCC,rosh • Module Size: 250mm*250mm • Place Of Origin: Shenzhen China



More Images



Product Description

P4.81 Indoor Rental LED Screen Best Resolution led module 3in1 window screen led module

Product feature:

- 1 . The new structure design enables diversified installation to meet the hanging-up and stacking requirements, can be applied to achieve a variety of different occasions to meet various application requirements
- 2 . User-friendly design, more convenient installation, more efficient and secure; High strength, high toughness, and deformation; More reliable cabinet patchwork and cable connection .
- 3 . Cabinets adopt rapid assembling sets, Which can be beautiful but also a real rapid disassembling .
- 4 . Good thermal design. Taking structural heat emitting to keep the cabinet a excellent heat dissipation even no fan installation .
- 5 . The entire cabinet with die casting aluminum alloy material is more lightweight and practical .
- 6 . Compact base design, so that the whole screen space can be smaller a lot .
- 7. Higher IP rating; New system, High refresh rate, High brightness, True color output; Breathtaking gray level.
- 8 . Low . Has excellent heat dissipation design and performance . It is low noise and doesn't need external fan or air-condition. With the features of lightweight and low power consumption, it can reduce the labor cost of installation and operating cost .
- 9 . The same size cabinet can be compatible with different specification displays of different DOT pixels. (P3.9, P4.81, P5.2, P6.25) .

PRODUCT DESCRIPTION:

- 1, All die-cast aluminum, secure and nice in constitution.
- 2, Dust proof, IP 43.
- 3, Auto locking system ,super easy to assemble and disassemble .
- 4, Fan-less design with great structural heat dissipation function, achieving noise-free
- 5, High refresh Rate, flicker free(no scan lines) even under HD cameras, superior images are available for live events.
- 6, Large viewing angle, the panel viewing angle is up to 140, the vertical angle could reach 140, the image won't be out of shape and color cast between the rang.
- 7, Could be exact connected and easy to install and dismount.

Pixel Pitch	4.81mm	Pixel configuration	1R1G1B
Module size	250 x 250mm	Module resolution	60x60pixel
		, ,	2,500nits
	500x500mm		104x104pixel
Panel material	aluminum	Refresh rate	2200HZ
(IIIax/avg)			16.7milion
Gray scale per color	65536 level	Viewing angle (H/V)	140/140 (deg)
IP rating (Front/Rear)	IP43	Input voltage (AC)	110V ~ 240V
Operating temperature	-20°C ~+ 50°C	Operating humidity	10% ~ 90%
MTBF	10,000hours	Life Time	100,000hours

SOL COL UR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen