



Shopping Malls P6 LED Screen Panel Screen 6200nits Brightness High Precision And Unifor

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: CE,3C,FCC ,ROSH,ISO9001
- Model Number: P6 Outdoor
- Minimum Order Quantity: 1 Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month




Product Specification

- Color: Full Color
- Brightness: 6200nits
- Driver IC: MBI 5124
- Certificate: CE
- Uasge: Outdoor
- Place Of Origin: Shenzhen China



More Images



Product Description

P6 Outdoor led screen Panel HD Full Color SMD P6 LED Display Module / LED Screen / LED Video Wall

LED display feature :

1. **Light** : Cabinet Size 512mm x 512mm, weighs only 12.5kg .
2. **Thin** : Cabinet thickness between 36mm to 87mm .
3. **Fast** : Plug and play design . Cabinets are easy and quick to assemble without tools in short time.
4. **Precise** : the molding process of die-casting aluminum cabinet enclosure tolerances controlled within 0.1mm , the flatness of the entire screen and gap between cabinets is less than 0.5 mm.
5. **Easy** : random replacement of any cabinets inside the whole screen during broadcasting.
6. **Tolerance** : meet the assembling method from hoisting, fixed installation, ground piling installation, both capable to be used for indoor and outdoor .
7. **Stable** : Tested by strict requirement , capable of working under - 20 degrees to 60 degrees .
8. **Low** : low power consumption , low noise created , low transportation costs, and low installation costs .
9. **Indoor products** : high refresh , high gray - scale, high - contrast, vivid video effect .
10. **Outdoor products** : waterproof grade IP65 , certification through SGS .

Parameter

Unit Module	Item	Parameter
	Model Number	HX-P6-8S
	Module size	192mm*192mm
	Pixel pitch	6mm
	Pixels Density	27777Pixels /m2
	Pixel configuration	1R1G1B
	LED Package mode	SMD2727
	Pixel resolution	32dots(W)*32 dots(H)
	Max Power	20W
	Module thickness	17.05mm
	Weight	0.41kg
	Drive type	Constant drive
	Scan mode	1/8Scan 1/8scan
	Port type	HUB75-A
	rightness of white balance	≥6500cd/m2

Product Show



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen