



Wedding Led Video Wall Rental , Indoor Led Video Walls Stable Performance

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: CE,3C,FCC,ROSH,ISO9001
- Model Number: P8 Outdoor
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month




Product Specification

- Color: Full Color
- Brightness: 7000
- Warranty: 2 Years
- Certificate: CE,3C,FCC,ROSH
- Uasge: Outdoor
- Place Of Origin: Shenzhen China



More Images



Product Description

P8 Outdoor LED Video Wall 7000Brightness P8 Outdoor Waterproof Full Color Double Sided LED Display

Product Features:

- 1, High protection grade of front IP65/rear IP54, enables it to be used in any outdoor harsh environment.
- 2, High refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.
- 3, High brightness ensures the spectators far from the screen can still enjoy what is shown, even under direct sunlight.
- 4, Super wide viewing angle and have best view in different position, give you visual enjoyment.
- 5, SMD2727 technology could guarantee higher flatness and better performance.
- 6, Aviation plug and quick lock is used, bringing easier cables connection and quicker assembly of cabinets to save time.
- 7, Low power consumption and fast heat dissipation with dual channel heat dissipation
- 8, Support a series of detection functions, for example detection of cables failure, detection whether the door of cabinets closed or not, fans' speed monitoring, three-way voltage monitoring and temperature monitoring etc.
- 9, Widely used in outdoor advertising, toll gate, supermarket, shopping mall, sport game etc.

Parameter

Unit Module	Item	Parameter
	Model Number	SF-SS8-5-A
	Module size	320mm*160mm
	Pixel pitch	8mm
	Pixels Density	15625 Pixels/m2
	Pixel configuration	1R1G1B
	LED Package mode	Nationstar SMD3535
	Pixel resolution	40dots(W)*20dots(H)
	Max Power	30W
	Module thickness	22mm
	Module Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/5
	Port type	HUB75-A
	Brightness of white balance	≥7000 7500cd/m2
LED Cabinet	Dimension	960mm*960mm*100 mm
	Monomer Module Number	24pcs
	Power supply	5V/40A*4 pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	120mm*120mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	330W/
	Max.Power consumption	≤1100W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1200HZ
	Grey scale/colors	4096,16.7M Color 4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

Project Case



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen