

Full Color Outdoor Rental LED Display High Brightness Protection Level IP65 250 * 250mm

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHIAN
- Brand Name: SC
- Certification: CCC ISO14001 CE IP65
- Model Number: P3.91
- Minimum Order Quantity: Square Meters / 1 Piece
- Price: discuss
- Packaging Details: 5 Wooden box, Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Warranty: 2 Years
- CABINET: 500mm*500mm
- Scan: 16 Scan
- Color: Full Color
- Module Size: 250*250mm
- Module Resolution: 64*64dots
- Brightness: 4500CD
- Brand Name: SOL COLUR



Product Description

250mm*250mm P3.91 Indoor Rental Led Screen With Die-Cast Aluminum, Full color Good Quality

Our Product Advantages:

Protection level IP65, is full waterproof, dustproof, anti-corrosion and anti-ultraviolet, enable themselves to work in all weather conditions to guarantee durability, reliability and steady.

High brightness ensures the spectators far from the screen can still enjoy what is shown, even under direct sunlight.

Curvature adjustment from -15 to +15 is optional, could meet more requirements of clients about different shapes.

Silent design, superior heat dissipation, fanless design-fulfilling quiet working environment without noise

Product Specification:

| | | | |
|---------------------|----------------------------------|-----------------------|----------------------------|
| Model No. | P3.91 | Description | Outdoor Rental LED Display |
| Pitch | 3.91mm | Pixel Density | 65746 pixels/sq.m |
| Pixel Configuration | 1R1G1B | Pixel Type | SMD1921 |
| Module Size | 250*250mm | Module Resolution | 64*64 pixels |
| Cabinet Size | 500*500mm | Cabinet Resolution | 128*256 pixels |
| Drive Mode | 1/16 scan, constant current | Drive IC | MBI5124 |
| Brightness | 4500cd | Refresh Rate | 1920Hz |
| Grey Scale Level | 65536 | Contrast Ratio | 4000:1 |
| Viewing Angle | 150°(Horizontal), 120°(Vertical) | Best Viewing Distance | 3~50m |
| Protection Level | IP65 | Voltage | AC220V±10 , 50/60 Hz |

Project Show



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen