



## Commerical SMD3535 Led Stage Screen Big Led Screen For Stage 6500Nits

Our Product Introduction

for more products please visit us on sol-colur.com


### Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: CE,3C,FCC,ROSH
- Model Number: P8 Outdoor
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



### Product Specification

- Color: Full Color
- Brightness: 6500Nits
- Warranty: 2 Years
- Certificate: CE,3C,FCC,ROSH
- Uasge: Outdoor
- Driver IC: MBI5124
- Package Mode: SMD Nationstar
- Highlight: **Led Stage Screen 6500Nits ,  
6500Nits Big Led Screen For Stage ,  
SMD3535 Led Stage Screen**



### More Images



## Product Description

Commerical P8 Curved Led Panels , 6500Nits Brightness Led Outdoor Advertising Screens

### Product Features:

- 1, Pixel density is 15625 pixels per square meter, high resolution guarantee superior performance even with small screen size, thus could meet every kind of requirements from clients.
- 2, Protection level is IP65, is full waterproof, dustproof, anti-corrosion and anti-ultraviolet, enable themselves to work in all weather conditions to guarantee durability, reliability and steady.
- 3, High brightness ensures the spectators far from the screen can still enjoy what is shown, even under direct sunlight.
- 4, High refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.
- 5, Super wide viewing angle and have best view in different position (can be visible in most corners), could give you visual enjoyment in most corners.
- 6, SMD3535 technology could guarantee higher flatness and better performance.
- 7, Aviation plug and quick lock is used, bringing easier cables connection and quicker assembly of cabinets to save time.

### Parameter

Unit Module	Item	Parameter
	Model Number	SF-SS8-4-A
	Module size	256mm*128mm
	Pixel pitch	8mm
	Pixels Density	15625 Pixels /m2
	Pixel configuration	1R1G1B
	LED Package mode	Nationstar SMD3535
	Pixel resolution	32dots(W)*16dots(H)
	Max Power	25W
	Module thickness	22mm
	Module Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6000 6500cd/m2
LED Cabinet	Dimension	1024mm*768mm*100 mm
	Monomer Module Number	24pcs
	Power supply	5V/40A*4 pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	128mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	330W/
	Max.Power consumption	≤1100W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1200HZ
	Grey scale/colors	4096,16.7MColor 4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

**Application:**

Widely used in Advertising media, Concert, TV SHOW, Super mall, Entertainment, School, Government, Trading conversation, Commodity fair, Exhibition, Cinema, News conferences, Meeting room, Airport, Hotel, Station Hall and other Public Places.

**Project Cases**

**SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD**



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen