



High Refresh Rate Outdoor Advertising LED Display 4 Scan Mode Protection Level IP65

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHIAN
- Brand Name: SC
- Certification: CCC ISO14001 CE IP65
- Model Number: P8
- Minimum Order Quantity: Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box ,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Color: 1R1G1B
- Cabinet Size: 1024mm*768mm
- Scan Mode: 4 Scan
- Warranty: 2 Years
- Module Number: Outdoor P8
- Module SIZE: 256*128mm
- LED Lamp: Nation Star SMD2727
- Place Of Orign: Shenzhen, China



More Images



for more products please visit us on sol-colur.com

Product Description

Hot Sale, Waterproof P8 SMD Outdoor, Full Color Led Display ,High Refresh, Manufacturers.

Features and Application:

1. New design for advertising,in the past,all the advertisement is standing,while now all the advertisement can be mobile,therefore,it can have better advertisement effect.Instead of having fixed outdoor video displays in several locations,a mobile LED display installed on a truck that you can park in different strategic points of the city,at peak times of each day,in addition,if you are an event management company and need to have a led display move anywhere,a truck-mounted led display would be the perfect answer.
2. Portable led display.Owing to the truck,it is very easy to move from one place to another.
3. Our LED display can be installed in different areas all over the world.Low temperature as -20°C and high temperature as +60°C,high humidity and high salty air environment such as seaside,out cabinet is moisture-proof and salt-proof.
4. High brightness DIP LED is widely used for mobile truck led display with weatherproof design,so can be used outdoor with cute weather.Meanwhile,vivid color performance and high conformity would bring an excellent display effect for the event.

Project Specification:

	Item	Parameter
Unit Module	Model Number	SF-SS8
	Module size	256mm*128mm
	Pixel pitch	8mm
	Pixels Density	15625/m ²
	Pixel configuration	1R1G1B
	Package mode	SMD2727
	Pixel resolution	32dots(W)*16dots(H)
	Max Power	25W
	Module thickness	22mm
	Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6200 6500mcd/m ²
Cabinet	Dimension	1024mm*768mm*100 mm
	Monomer Module Number	24pcs
	Power supply	5V/40A*4pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	128mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W)110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	330W/
	Max.Power consumption	≤1100W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above p4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1920HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥100000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

Products Demonstration:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen