# SHENZHEN SOL COLUR DISPLAY CO.,LTD

# High Refresh P3.91mm Outdoor Rental LED Display Screen Die - Casting **Aluminum**

#### **Basic Information**

. Place of Origin: SHENZHEN CHIAN

. Brand Name: SC

CCC, ISO14001, CE, IP65 · Certification:

P3.91 Model Number:

• Minimum Order Quantity: Square Meters / 1 Piece

• Price: Negotiable

Wooden box, Flight Case Packaging Details: • Delivery Time: 10 days after received deposit Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 5000 Square Meter/Square Meters per



## **Product Specification**

• Pixel Pitch: 3.91mm

 CABINET Size: 500mm\*500mm

16 Scan Drive Mode: 1R1G1B · Color: Brand Name: SOL COLUR Cabinet Materrial: Aluminum

Module Number: Rental LED Display P3.91

. Place Of Orign: Shenzhen, China



### More Images



#### **Product Description**

Fanless design, excellent natural heat dissipation achieves zero noise, providing quiet working environment, best choice for indoor rental e

#### **Produce Specification:**

	Item	Parameter
	Model Number	HX-P3.91-16S
	Module size	250mm*250mm
	Pixel pitch	3.91mm
	Pixels Density	65536/m2
	Pixel configuration	1R1G1B
Unit Module	Package mode	SMD1921
	Pixel resolution	64dots(W)*64 dots(H)
	Max Power	38W
	Module weight	0.7kg
	Drive type	Constant drive
	Scan mode	1/16scan
	Port type	HUB75-A
	Brightness of white balance	≥4800cd/m2

Cabinet	Dimension	500mm*500mm
	Monomer Module Number	4pas
	Power supply	5V/40A*1pas
	Protection grade	IP65
	Pixel per cabinet	128mm*128mm
	Best viewing distance	2M 18M
	Best viewing angle	160°(W) 120°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	65m

	Working voltage	AC220V±10%
	Average Power consumption	320W/
Power	Max.Power consumption	≤800W/
	Current	≤20mA(single LED)
	CPU	Pentium4 or above P4
Control system	Operation system	WIN98/2000/NT/XP/WIN7

#### Product Features:

 $Front \ or \ rear \ maintenance, modules \ and \ control \ box \ can \ be \ installed \ and \ maintained \ from \ either \ front \ or \ rear.$ 

Protection level IP65, is full waterproof, dustproof, anti-corrosion and anti-ultraviolet, enable themselves to work in all weather conditions to guarantee durability, reliability and steady.

There are handles on modules and cabinets, much more convenient for assemble, disassemble and moving.

LCD displays on back of cabinet could show working condition of each panel, including temperature, voltage, single using time, accumulated using time and DVI signal. Alignment hole and location pin design for installation could achieve extreme precision between cabinets, besides module shaping one time, get seamless splicing and assemble easier

Cabinet size is 500\*500mm, and weight is only 8kg/pc, very light and slim, convenient in transporting and and installation, thus save labor cost and avoid wasting much time, very suitable for flow shows and rents.

Fanless design, excellent natural heat dissipation achieves zero noise, providing quiet working environment, best choice for indoor rental events.

High refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.

Project Case:



# SOL COL UR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen