




Indoor Stage Rental Led Display Screen , Commercial Led Digital Advertising Display

Our Product Introduction

for more products please visit us on sol-colur.com

Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: CE,3C,FCC,ROSH,ISO9001
- Model Number: P6.25 Indoor
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Color: Full Color
- Brightness: 5100Nits
- Warranty: 2 Years
- Certificate: CE,3C,FCC,ROSH,ISO9001
- Uasge: Indoor
- Driver IC: MBI5124
- Package Mode: SMD Nationstar



More Images



Product Description

Indoor Rental Led Screen 250*250mm Module Rental use Indoor LED video wall panel p6.25mm

Product Quick Details:

- A, Die-cast aluminum cabinet 500x1000mm and 500X500mm
- B, Slim and Light
- C, Seamless splicing

Product Features:

- 1, Fanless design, excellent natural heat dissipation achieves zero noise, providing quiet working environment, best choice for indoor rental events.
- 2, User-friendly locking system, aviation plug and three handles on each cabinet makes disassembly and maintenance easy and convenient. Unique anti-burial design to avoid the patchwork.
- 3, SMD guarantee super wide viewing angle, higher flatness and better performance, offers you clear and natural images in all directions.
- 4, IC MBI5124 is used, high refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.

Parameter

Led Module

1 LED Light Parameter

LED	LED brand	LED type	wave Length(nm)	Average Brightness (mcd)	Test Condition
Red(R)	Sanan	SMD 3528	615-625nm	150-300mcd	25°C,20mA
Green(G)	Huacan		515-535nm	350-550mcd	25°C,10mA
Blue(B)	Huacan		465-475nm	50-85mcd	25°C,5mA

2 Pixel/Module

No	Item	Parameter
1	Pixel Pitch	6.25 mm
2	Pixel Configuration	1R1G1B / R:G:B=3:6:1
3	LED Lamp	Full color
4	Density	28224dot/m ²
5	Module Size	250*250mm
6	Module Pixel	42*42=1764dot
7	Module Thickness	15mm
8	Module Weight	0.45kg
9	Module Power	≤25W
10	Drive Valtage	DC5V
11	Module Electric Current	6.2-6.4A
12	PortType	HUB-38D/B

3 Screen Parameter

No	Item	Parameter
1	Standard Cabinet Size	500mm*500mm*75mm /1000mm*1000mm*75mm
2	Cabinet Weight	5.5KGS/13.75KGS
3	Brightness/Adjustment	≥800cd/m ² , Level 16- Automatic / Level 100-Manual operation
4	View Angle	≥120°(Vertical),≥120°(Horizontal)
5	Best View Distance	5-15m
6	Grey Scale	Within 65536 Step
7	Frame Frequency	≥60Hz
8	Refresh Rate	≥720Hz
9	Signal Input Source	Composite, S-video, Component, VGA, DVI, HDMI, SDI, HD-SDI
10	Scan Mode	1/10Scan
11	Drive IC	5020
12	Module Qty / M ²	16
13	Display Color Qty	16777216
14	Continuous Working Time	>24(Hrs)
15	Screen Lifespan	>100,000(Hrs)
16	MTBF	>5000(Hrs)
17	Max. power consumption	500W/
18	Ave. power consumption	160W/
19	Out of control pixel rate	≥3/10,000(discrete distribution)

20	Control Distance	100M(Ethernet) 500M(Multi-fiber) 10KM(Single-fiber)
21	Flatness	Screen Surface≤0.5mm,Pixel Pitch≤0.3mm
22	Operation Temperature	-10°C +50°C
23	Working Humidity	10% 98%RH
24	Storage Temperature	-40°C +85°C
25	Software Connection	Standard Computer Connection, Compatible With Windows,Unix,Novell
26	protection system	Over temperature/overload/power/image compensation/nonlinear correction
27	Working Voltage	200~240 V
28	Dielectric Strength	50HZ/1500V(AC RMS)/1min
29	Temperature Rise	Metal≤40K,Insulation≤65K , After Heat Balance
30	IP Grade	IP65
31	Computer display mode	1024*768
33	Media Player	LED Professional Media Player

Project Cases



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen