



Waterproof Led Large Screen Display , Super Slim Led Backdrop Screen Rental

Our Product Introduction

Basic Information

- Place of Origin: SHEN ZHEN CHINA
- Brand Name: SC
- Certification: CCC CE IP65 ROSH
- Model Number: P2.5
- Minimum Order Quantity: Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: 5 Wooden box, Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Pixel Configuration: 1R1G1B
- Led Lamp: Nation Star SMD2121
- Module Size: 160mm*160mm
- Module Scan: 32s
- Weight: 1.5kg
- Brand Name: SOL COLUR
- IC: MBI
- Refresh Frequency: 1080HZ
- Protection Level: IP45
- Cabinet Thickness: 22mm



More Images



for more products please visit us on sol-colur.com

Product Description

Die- cast Aluminum, Rental LED Display, Indoor Led Display Screen, Full Color P2.5, 160mm*160mm P2.5

Our Services:

Pre-sale service:

1. Reply enquiries in 24 hours.
2. Market research and forecast for customer.
3. Provide unique and professional solutions based on customer's requirement.
4. Data sheet and samples offer.

In-sale service:

1. Tracking report in producing.
2. Quality test report for every order.
3. Photos and videos as per customer's requirement.
4. Free spare parts.

After-sale service:

1. One year replacement, two years warranty.
2. Maintenance guidance and problem solution supplied in 48 hours.
3. Free technician training.
4. Full set of documents free of charge, which including installation guidance, software operation manual, easy maintenance manual and control system software CD and so on.

Application:

Widely used in stage, concert, TV studio, wedding, conference, ceremony gala, exhibition presentation, commercial advertising and other indoor rental events.

Product Specification:

--

P2.5 Indoor LED Display	
Pixel Pitch(mm)	2.5mm
Pixel configuration	1R1G1B / SMD2121 Black lamp
Pixel density	160000dots/sqm
Brightness	≥1200cd/sqm
Module size(W*H)	160mm×160mm
Module Resolution (W*H)	64 dots x 64dots
Module weight	300g
Cabinet size (W*H)	480mm×480mm
Drive IC	MBI5124
Drive mode	1/24scan
Viewing Angle(V/H)	140 °C
Grey Scale	65536 degree
Life time	>100,000 Hours (80%)
MTBF	>50,000 Hours
Operating Voltage	AC110V/220V±10%
Screen Power Consumption	Max: 1000w/sqm; Average:330w/sqm
Input Power Frequency	50/60Hz
Operating temperature	-30--60°C
Humidity	10%-95%
Refresh Rate	≥1920HZ
Control Method	Synchronized with computer monitor
Color Temperature	6500K-9500K
LED control system	LINSN,Nova-star,Colorlight is selectable
Control Distance	100 m (no repeating); Optical fiber transmission: 500m-15km
Accepting signal with video processor	PAL/NTSC/SECAM,S-Video;VGA;RGB;Composite Video;SDI
Systems Operating Platform	Windows Xp / Windows 7 / windows 8 /8.1 / windows 10

Project Case:





+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen