



SMD P10 Flexible Cylindrical LED Display Slim And Light Weight For Outdoor Advertising

Our Product Introduction

for more products please visit us on sol-colur.com

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: SC
- Certification: CCC IP68 CE ISO9001 ROHS
- Model Number: Outdoor SMDP10
- Minimum Order Quantity: Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box, Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Place Of Origin: Shenzhen, China
- Module Size: 320mm*160mm
- Brightness: 6000
- Color: 1R1G1B
- Pixel Resolution: 32*16dots/sqm
- Max Power: 35W
- Cabinnet Resolution: 96*96dots
- Highlight: SMD P10 Cylindrical LED Display,
SMD P10 Cylindrical LED Display,
Light Weight Cylindrical LED screen



More Images



Product Description

Pixel 10mm, OutdoorSMD P10, Flexible led cylindrical screen display, Shenzhen Manufacturers

Product Quick Details:

Pixel pitch: 10mm
Protection level: IP65
Slim and light weight

Product Features:

Project Show:



Cabinet size is 640*640mm, featured very light and slim, makes much easier for transporting, installation and movement, could save your cost and time.

SMD 3535 is used, high protection grade of front IP65/rear IP54, enables it to be used in any outdoor harsh environment.

Fanless design, excellent natural heat dissipation achieves zero noise, providing quiet working environment, best choice for indoor rental events.

Using die-casting aluminum mold forming, cabinet dimensional tolerance is controlled within 0.01mm, besides alignment hole and location pin design for installation could achieve extreme precision between cabinets, get seamless splicing and assemble easier

Handlers design, cabinet has handlers on top and sides, more convenient to assemble and maintenance.

IC MBI5124 is used, high refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.

High brightness ensures the spectators far from the screen can still enjoy what is shown, even under direct sunlight.

General Information:

Model No.	M10-O	Description	Outdoor Rental LED Display
Pitch	10MM	Pixel Density	10000 pixels/sq.m
Pixel Configuration	1R1G1B	Pixel Type	SMD3535

Product Parameter:

ITEM	SPECIFICATION
Module Size	320*160mm
Module Resolution	32*16
Cabinet Size	640*640mm
Cabinet Material	Die-casting aluminum
Drive Mode	1/2 scan, constant current
IC	MBI5124
Brightness	6000CD/SQ.M(adjustable)
Refresh Rate	1920Hz
Frame Frequency	50&60Hz
Grey Scale Level	65536(adjustable)
Color Temperature	3200~9300K(adjustable)
Contrast Ratio	4000:1
Viewing Angle	150°(Horizontal),120°(Vertical)
Best Viewing Distance	10~100m

Protection Level	IP65
Power Consumption (Max)	700W/M ²
Power Consumption (Avg)	300W/M ²
Control System	Synchronous/Asynchronous Control System
PC System	Windows 7, Windows 98, 2000, XP, ME, NT

Warranty:

2 years quality guaranteed, necessary design drawing and user manual step by step will be offered to you

SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen