# High Refresh Rate Hd Led Video Wall, Full Color Large Video Wall **Displays**

# **Basic Information**

• Place of Origin:

### SHENZHEN CHINA

- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



5000 Square Meter/Square Meters per

- Negotiable
- Wooden box,Flight Case
  - 10 days after received deposit

Month

2 Years

SC

- L/C, D/A, D/P, T/T



# **Product Specification**

- Warranty:
- Usage:
- Brightness:
- Color:
- Module Number:
- Placr Of Orign:
- Protection Grade:

Outdoor
8000
Full Color
Dip P16
SHENZHEN, CHINA
IP65



### More Images





### **Product Description**

### Chinese Manufacturers, High BrightnessDIP P16, Energy Saving Outdoor Waterproof DIP P16.

### Product Features:

High brightness 8000CD ensures the spectators far from the screen can still enjoy what is shown, even under direct sunlight.

High protection grade of front IP65/rear IP54, enables it to be used in any outdoor harsh environment.

High refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.

Super performance/cost ratio offers you both top notch quality and reasonable price, maximizing the value of your investment.

Aviation plug and quick lock is used, bringing easier cables connection and quicker assembly of cabinets to save time.

Support a series of detection functions, for example detection of cables failure, detection whether the door of cabinets closed or not, fans' speed monitoring, three-way voltage monitoring and temperature monitoring etc.

Low power consumption and fast heat dissipation with dual channel heat dissipation

#### Application:

Widely used in Advertising media, Concert, TV SHOW, Super mall, Entertainment, School, Government, Trading conversation, Commodity fair, Exhibition, Cinema, News conferences, Meeting room, Airport, Hotel, Station Hall and other Public Places.

#### Product Parameter:

ITEM	SPECIFICATION
Pixel Pitch	16mm
Pixel Density	3096
Pixel Configuration	1R1G1B
Pixel Type	DIP346
Module Size	256*256mm
Module Resolution	16*16
Drive Mode	static scan, constant current
IC	SM16106SC
Brightness	8000CD/SQ.M(adjustable)
Refresh Rate	3000Hz
Frame Frequency	50&60Hz
Grey Scale Level	65536(adjustable)
Color Temperature	3200~9300K(adjustable)
Contrast Ratio	4000:1
Viewing Angle	100°(Horizontal),45°(Vertical)
Best Viewing Distance	16~100m
Protection Level	IP65
Power Consumption (Max)	850W/M <sup>2</sup>
Power Consumption (Avg)	300W/M <sup>2</sup>
Input Port	DVI Connector (DVI Port)
Input Signal	RF, TV, S-VIDIEO, RGB, VGA, DVI, HDTV, PAL, YUT, YC, COMPOSTITION

# SOL COL UR SHENZHEN SOL COLUR DISPLAY CO., LTD

+86 13751136904

chenhao@sol-colour.com

Sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen