




Full Color DIP16 Outdoor LED Video Screen Module 256*256mm Wide Viewing Angle

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: SC
- Certification: CCC IP68 CE ISO9001 ROHS
- Model Number: Outdoor Energy Saving DIP P16
- Minimum Order Quantity: Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box, Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T
- Supply Ability: 5000 Square Meter/Square Meters per Month




Product Specification

- Warranty: 2 Years
- Usage: Outdoor
- Brightness: 8000
- Color: Full Color
- Weight: 0.5kg
- Module Size: 256*256mm
- Brand Name: SOL COLUR
- Highlight: DIP16 LED Video Screen Module,
DIP16 outdoor display module,
LED Video Screen Module 256*256mm



More Images



for more products please visit us on sol-colur.com

Product Description

Waterproof Cabint Full Color DIP16 Outdoor Led Screen Module 256*256mm, DIP16 Led Advertising Outdoor

Features and Application:

1. New design for advertising, in the past, all the advertisement is standing, while now all the advertisement can be mobile, therefore, it can have better advertisement effect. Instead of having fixed outdoor video displays in several locations, a mobile LED display installed on a truck that you can park in different strategic points of the city, at peak times of each day, in addition, if you are an event management company and need to have a led display move anywhere, a truck-mounted led display would be the perfect answer.
2. Portable led display. Owing to the truck, it is very easy to move from one place to another.
3. Our LED display can be installed in different areas all over the world. Low temperature as -20°C and high temperature as +60°C, high humidity and high salty air environment such as seaside, our cabinet is moisture-proof and salt-proof.
4. High brightness DIP LED is widely used for mobile truck led display with weatherproof design, so can be used outdoor with any weather. Meanwhile, vivid color performance and high conformity would bring an excellent display effect for the event.
5. Widely used in tent market, ideal for advertising in busy street or intersections, conference, shows, concerts, sporting event, grand opening, exhibitions, political rallies, elections etc.

ZS16 outdoor full-color technology parameters:

Item	Parameter
Unit Module	Model Number
	SF-ZS16-0S-A-J
	Module size
	256mm*256mm
	Pixel pitch
	16mm
	Pixels Density
	3906dots/m ²
	Pixel configuration
	1R1G1B
	Package mode
	DIP346
	Pixel resolution
	16dots(W)*16 dots(H)
Cabinet	Max Power
	35W
	Module thickness
	33mm
	Weight
	0.5kg
	Drive type
	Constant drive
	Scan mode
	Quiet
	Port type
	HUB75
	Brightness of white balance
	≥8000cd/m ²
Cabinet	Dimension
	1024mm*1024mm*100 mm
	Monomer Module Number
	16pcs
	Power supply
	3.8V/40A*2pcs
	Thermal discharge
	fan 2pcs
	Pixel per cabinet
	64mm*64mm
Power	Best viewing distance
	16M 30M
	Best viewing angle
	110°(W)55°(H)
	Temperature
	storage:-35°C +85°C working:-20°C +50°C
Control system	Relative humidity
	10%-95%
	Thickness
	125mm
Main technical parameter	Working voltage
	AC220V±10%
	Average Power consumption
	350W/
Control system	Max.Power consumption
	≤800W/
	Current
	≤20mA(single LED)
Control system	CPU
	Pentium4 or above P4
	Operation system
Main technical parameter	WIN98/2000/NT/XP/WIN7
	Control method
	Synchronization
Main technical parameter	Driving device
	Constant drive
	Refresh frequency
	≥1200HZ
	Grey scale/colors
	4096 4096gray level/16.7M colors
Main technical parameter	MTBF
	≥9000hours
Main technical parameter	Power switch
	Automatic switch
Main technical parameter	Display Mode
	≥1024*768

Project Cases:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen