




Commercial Large Concert Indoor LED Display Module P2 Led Module 1R1G1B

Our Product Introduction

for more products please visit us on sol-colur.com


Basic Information

- Place of Origin: SHENZHEN
- Brand Name: SC
- Certification: ISO9001,FCC,IP65,3C ,ROSH9001
- Model Number: P2 Indoor
- Minimum Order Quantity: 1 Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case ,carton
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Product Model: P2 Mm
- Module Size: 128mm*128mm
- Uasge: Indoor
- Module Size: 128*128 Mm
- Pixel Configurature: 1R1G1B
- Power Supply: Meanwell
- Pixel Density: 1250000dots/
- Viewing Angle: Level \geq 160°Optional
- Cabinet Size: 512*512mm
- Modules Weight: 0.3kg
- Highlight: **P2 Led Module 1R1G1B,
1R1G1B Indoor LED Display Module,
Commercial P2 Led Module**



More Images

512mmx512mm



Product Description

Large Full Color Indoor Concert Advertising Rental Display Price P2 LED Screen For Sale

Product Quick Details:

Pixel pitch: 2mm
IC: MBI5153
Refresh rate: 3840Hz
Brightness: 800CD

Product Features:

- 1, High quality SMD 1010 with low failure is used, it has a great performance in stability, lowest light malfunction, great color consistence as well as heat dissipation.
High grey scale under low brightness: The high quality full black leds, together with black mask, achieves clear and crystal picture.
- 2, High refresh rate 3840HZ, MBI 5153 is used, remove ghost without trailing, could meet high-end demands of clients, such as TV studio.
- 3, Ultra high resolution: 250000 dots per square meters, super clear, gives you big visual enjoyment even with small size.
- 4, Die-cast aluminum with CNC is finished, the dimension tolerance of less than 0.01mm, and module shaping one time, the machining accuracy of + 0.01mm, easy to realize seamless splicing.

Application

Rental use TV showing for shopping mall, Rental LED for promotion, Cinema Movies

Description

Smaller pitch, Clear Viewing distance, HD LED display, minimum viewing distance 2m.

Parameter

Pixel pitch :2mm	Module size : 128mm*128mm	Cabinet size :512x512x75(mm)
Physical density : 250000dots/	Pixel configuration: 1R1G1B	Modules resolution: 64*64=4096 DOTS
Modules weight: c		
Cabinet resolution :256X256	Cabinet 0.262144m²	
MAIN TECHNICAL PARAMETERS		
Best viewing distance :2m 15m	Viewing anglec	vertical≥120°Optional
Average power consumption 400W/	Maximum power consumption 800w/	Control mode: synchronous control
Display card: DVI	Driving method :1/32 scanning	Frame Frequency ≥60Hz
Refresh frequency ≥1920Hz	Equilibrium brightness ≥800cd/	Display working voltage(VAC)
Brightness adjustment	Lighting sensor adjust automaticly	16 grade adjustable
Adjust by bands with software:100 grade adjustable		
Computer system		
WIN98,WINXP,WIN2000,etc		
Input signal		
RF,S-Video,RGB,RGBHV,YUV,YC,COMPOSITION		
Control system		
PCTV nonlinearity card, DVI display card,Linsn control system		
Mean free error time ≥5000 hours	Lifetime: 75000 100000 hours	Pixel out of control rate 0.0002 one case
Project classification: PH1.923-26S	Package : SMD 3in1	LED SMD 1515

◆◆ Our Advantage ◆◆◆◆

1. Provide free technology support by email/video call/remote control. If need, can send engineer to your country.
2. Training for 2 Persons for installation and maintenance in factory for free.
3. We are not just the seller of the screen, but also your partner who will supply you comprehensive solution !!!

Project Cases



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen