



OEM Small Pixel Pitch LED Display P1.5 Led Screen Drive IC MBI5153 240X240mm Module

Our Product Introduction

for more products please visit us on sol-colur.com

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: SC
- Certification: ,ROSH, FCC.3C,ISO9001,IP65
- Model Number: P1.5
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month




Product Specification

- Usage: Indoor
- Refresh Rate: 3840HZ
- Warranty: 2 Years
- Model Number: P1.5
- Module Size: 240X240mm
- Place Of Origin: Shenzhen China
- Pixel Configuration: 1R1G1B
- IC: MBI5153
- Pixel Density: 444444 Dots/sq.m
- Cabinet Size: 480*480mm
- Highlight: Small Pixel Pitch LED Display P1.5,
OEM Small Pixel Pitch LED Display,
OEM P1.5 Led Screen



More Images



Product Description

Mobile Video Shows Small Pixel Pitch LED Display Drive IC MBI5153 240 X 240mm Module

Product Features:

- 1, Ultra high resolution: 444444 dots per square meters, super clear, gives you big visual enjoyment even with small size.
- 2, Die-cast aluminum with CNC is finished, the dimension tolerance of less than 0.01mm, and module shaping one time, the machining accuracy of + 0.01mm, easy to realize seamless splicing.
- 3, Perfect display effect: 160° super wide horizontal and vertical viewing angle covers more potential customers. The broadcasting pictures are stable with no scanning line, and the edge of image is sharp and clear when dealing with dynamic pictures.
- 4, High quality SMD 1010 with low failure is used, it has a great performance in stability, lowest light malfunction, great color consistence as well as heat dissipation.
- 5, High grey scale under low brightness: The high quality full black leds, together with black mask, achieves clear and crystal picture.
- 6, High refresh rate 3840HZ, MBI 5153 is used, remove ghost without trailing, could meet high-end demands of clients, such as TV studio.
- 7, Fanless design, excellent natural heat dissipation achieves zero noise, providing quiet working environment, best choice for indoor rental events.

General Information:

Model No.	Q1.5-I	Description	HD LED Display
Pitch	1.5MM	Pixel Density	444444 pixels/sq.m
Pixel Configuration	1R1G1B	Pixel Type	SMD1010, Black LED

Module Information:

Module Size	240*240mm	Module Resolution	160*160 pixels
-------------	-----------	-------------------	----------------

Cabinet Information:

Module Component	W:2*H:2pcs=4pcs
Cabinet Size	480*480mm
Cabinet Resolution	320*320 pixels
Cabinet Material	Die-cast Aluminum
Service Access	Back

Product Parameter:

ITEM	SPECIFICATION
IC	MBI5153
Drive Mode	1/32 scan, constant current
Brightness	800CD/SQ.M(adjustable)
Refresh Rate	3840Hz
Frame Frequency	50&60Hz
Color Processing Level	16 bit
Grey Scale Level	65536(adjustable)
Color Temperature	3200~9300K(adjustable)
Contrast Ratio	4000:1
Video playback capabilities	2KHD, 4KHD
Viewing Angle	160°(Horizontal), 160°(Vertical)
Brightness / chromaticity uniformity	≥97%
Best Viewing Distance	1~50m
Power Consumption (Max)	800W/M ²
Power Consumption (Avg)	250W/M ²
Working Temperature/Humidity	-20°C~60°C/10%~85%RH(non-condensing)
Storage Temperature/Humidity	-20°C~60°C/10%~85%RH(non-condensing)

Product Show



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen