



HD Electronic Led Backdrop Screen , High Brightness Indoor Stage Led Screen

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: SC
- Certification: ROHS, FCC.3C,ISO9001,IP65
- Model Number: P3.91 Indoor
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



P3.91室内全彩屏 (P3.91 indoor full-color led display)

Product Specification

- Usage: Indoor
- Refresh Rate: 3840HZ
- Warranty: 2 Years
- Model Number: P3.91
- Module Size: 250X250mm
- Place Of Origin: Shenzhen China
- Pixel Configuration: 1R1G1B
- IC: MBI5124
- Cabinet Size: 500*500mm
- Highlight: Indoor Stage Led Backdrop Screen ,
High Brightness Indoor Stage Led Screen ,
HD Electronic Led Backdrop Screen



Product Description

HD Electronic RGB P3.91 LED Video Wall Rental Nova Controller For Indoor Stage

Product Quick Details:

A, Die-cast aluminum cabinet 500x1000mm and 500*500mm

B, Wide viewing angle

C, Seamless splicing

Product Features:

1, here are three handles for lifting cabinets, aviation plug and fast lock on each side is equipped, makes very convenient and comfortable for fast installation by one person without tools, besides guarantee seamless installation and keep smoothly

2, Die-cast aluminum with CNC is finished, the dimension tolerance of less than 0.01mm, and module shaping one time, the machining accuracy of + 0.01mm, easy to realize seamless splicing.

3, Use special heat dissipation, quiet working without fans.

4, Pixel density is 65746 dots per square meter, high resolution brings HD visual effect.

5, SMD guarantee super wide viewing angle, higher flatness and better performance, offers you clear and natural images in all directions. high quality full black leds, together with black mask, achieves clear and crystal picture.

6, Alignment hole and location pin design for installation could achieve extreme precision between cabinets, seam splicing is less than 0.05mm.

7, High refresh rate, high grey scale level and high accurate color consistency guarantee the vivid pictures and perfect videos.

General Information:

Model No.	U3.91-I	Description	Indoor Rental LED Display
Pitch	3.91MM	Pixel Density	65746 pixels/sq.m
Pixel Configuration	1R1G1B	Pixel Type	SMD2121, Black LED

LED Information:

Color	Wave Length	Brightness
Red	620~625nm	120~156mcd
Green	520~525nm	280~364mcd
Blue	465~470nm	40~52mcd

Module Information

Module Size	250*250mm	Module Resolution	64*64 pixels
-------------	-----------	-------------------	--------------

Cabinet Information:

Module Component	W:2'H:4pcs=8pcs
Cabinet Size	500*1000*75mm
Cabinet Resolution	128*256 pixels
Cabinet Weight	13.5kg/pc
Service Access	Back

Product Parameter:

ITEM	SPECIFICATION
Pixel Configuration	1R1G1B
Pixel Type	Black SMD2121
Module Size	250*250mm
Module Resolution	64*64
Cabinet Size	500*1000*75mm
Cabinet Weight	13.5kg/pc
Drive Mode	1/16 scan, constant current
IC	MBI5124
Brightness	1500CD/SQ.M(adjustable)
Refresh Rate	1920Hz
Frame Frequency	50&60Hz
Grey Scale Level	65536(adjustable)
Color Temperature	3200~9300K(adjustable)
Contrast Ratio	4000:1

Viewing Angle	150°(Horizontal), 120°(Vertical)
Best Viewing Distance	3~50m
Cabinet Flatness	≤0.2mm
MTBF	≥5,000 hours
Life-Span	100,000 hours
Protection Level	IP31
Power Consumption (Max)	800W/M ²
Power Consumption (Avg)	300W/M ²
Voltage	AC 100V~240V, 50/60 Hz

Application:

Widely used in stage, concert, live on TV, wedding, conference, ceremony gala, exhibition presentation and commercial advertising etc.

Project Cases



SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen