



High Resolution Stage LED Display Video Wall Rental Die Casting Aluminum Seamless Splicing

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: SC
- Certification: ROHS, FCC.3C,ISO9001,IP65
- Model Number: P3.91 Indoor
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: Wooden box,Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Usage: Indoor
- Refresh Rate: 3840HZ
- Warranty: 2 Years
- Model Number: P3.91
- Module Size: 250X250mm
- Place Of Origin: Shenzhen China
- Pixel Configuration: 1R1G1B
- IC: MBI5124
- Cabinet Size: 500*500mm
- Highlight: **Seamless Splicing Stage LED Display,
Die Casting Aluminum Stage LED Display,
High Resolution Stage LED Display**



for more products please visit us on sol-colur.com

Product Description

P3.91 Indoor Led Video Wall Rental 500 X 500 Mm High Contrast And Uniform

Product Quick Details:

A, Die-cast aluminum cabinet 500x1000mm and 500*500mm

B, Wide viewing angle

C, Seamless splicing

Product Advantage

1. Featured like high precision, lightweight, ultra thin and die casting aluminum.
2. Offer excellent contrast and image quality.
3. Robust structure and high quality materials allow LED screen to have amazing durability.

Product Specification:

Model No.	T3.91-I
Pixel pitch	3.91MM
Pixel density /sq.m	65536dots
LED configuration	1R1G1B SMD 2020
Module size	288mm x 288 mm
Cabinet size	500*500mm
Panel resolution	128*128dots
Scan way	1/16
Refresh rate	2000Hz
Panel weight	8kg
Brigtness	1000 CD / M ²
Max. power consumption	600 W/Panel
Avg. power consumption	100w/panel
Input voltage	AC 110-220 V (+-5 %)
Blind dot rate	≤0.01%
IP rating	IP3X
Panel material	Plastic
Working temperature	-20- + 60 °C
Working humidity	10-90% RH
Driving IC	MBI
Led chip	Nationstar
Lifetime	100,000h
Certification	CE,ROHS
Control system	Novastar / Linsn
Operating system	Windows / Me / 200 NT/XP
Minimum viewing distance	4m
Frame rate	50 - 60 Hz
Warranty	2 years

Application:

Widely used in stage, concert, live on TV, wedding, conference, ceremony gala, exhibition presentation and commercial advertising etc.

Project Cases



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen