



P8 Outdoor LED Wall Screen Advertising LED Display Panels

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: SC
- Certification: CCC IP68 CE
- Model Number: outdoor SMDP8
- Minimum Order Quantity: Square Meters / 1 Piece
- Price: Negotiable
- Packaging Details: Wooden box, Flight Case
- Delivery Time: 10 days after received deposit
- Payment Terms: L/C, D/A, D/P, T/T
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320*160mm
- Brightness: 6000-6500nits
- Control Method: Synchronization
- Color: 1R1G1B
- Module Number: Outdoor P8
- Led Package: Nationstar SMD3535
- Warranty: 2 Years
- Pixel Resolution: 32dots(W)*16dots(H)
- Highlight: **P8 Outdoor LED Wall Screen,
P8 Outdoor LED Display Panels,
Advertising LED Display Panels**



Product Description

P8 Outdoor LED Wall Screen Advertising LED Display Panels

Product Specification:

Item	Parameter
Unit Module	Model Number
	SF-SS10 -2-A
	Module size
	320mm*160mm
	Pixel pitch
	10mm
	Pixels Density
	10000dots/m2
	Pixel configuration
	1R1G1B
	LED Package mode
	NationStar SMD3535
	Pixel resolution
	32dots(W)*16dots(H)
LED Cabinet	Max Power
	35W
	Module thickness
	22mm
	Weight
	0.37kg
	Drive type
	Constant drive
	Scan mode
	1/2
	Port type
	HUB75-A
	Brightness of white balance
	≥6800 7200cd/m2
LED Cabinet	Dimension
	960mm*960mm*100 mm
	Monomer Module Number
	18pcs
	Power supply
	5V/40A*4 pcs
	Thermal discharge
	fan 2pcs
	Pixel per cabinet
	96mm*96mm
Power	Best viewing distance
	8M 15M
	Best viewing angle
	120°(W) 110°(H)
Power	Temperature
	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity
	10%-95%
Power	Thickness
	122mm
	Working voltage
	AC220V±10%
Power	Average Power consumption
	300W/
	Max.Power consumption
	≤800W/
Control system	Current
	≤20mA(single LED)
	CPU
	Pentium4 or above
Control system	Operation system
	WIN98/2000/NT/XP/WIN7
	Control method
Main technical parameter	Synchronization
	Driving device
	Constant drive IC
	Refresh frequency
	≥1200HZ
	Grey scale/colors
Main technical parameter	4096gray level/16.7M colors
	MTBF
	≥9000hours
	Power switch
Main technical parameter	Automatic switch
	Display Mode
	≥800*600/1024*768

Advantage :

- 1) With good lightening accordance and no mosaic
- 2) Led advertising board can play different formats of image files, flash, WAV/MIDI, video signal from TV, video signal from video and other equipment
- 3) Different video frequency can be changed freely at the same time, and the image can be enlarged and reduced
- 4) High brightness, and can be adjustable, meets the need of changing requirement of customer in environment
- 5) Uses real pixels rather than virtual pixels, better viewing effect

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen