



## High Brightness Outdoor Rental LED Display SMD Rental Screen P5 Constant Drive

### Our Product Introduction

#### Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: sol colur
- Certification: 3C Rosh CE
- Model Number: p5
- Minimum Order Quantity: 1pieces
- Price: Negotiable
- Packaging Details: Flight Case , Wooden Box , Carton
- Delivery Time: 15-20days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meters/ per month



#### Product Specification

- Product Name: P5
- Module Size: 160\*160mm
- Max Power: 25W
- Weight: 0.37kg
- Scan Mode: 1/8
- Drive Type: Constant Drive
- Highlight: **P5 Outdoor Rental LED Display ,  
SMD Outdoor Rental LED Display ,  
Constant Drive Outdoor Rental LED Display**

for more products please visit us on [sol-colur.com](http://sol-colur.com)

## Product Description

High brightness SMD rental led screen P5 outdoor rental led display / outdoor led screen

Product Description:

- 1) portable and practical always bring customer convenient and comfortable experience.
- 2) due to excellent flatness and nice uniformity of light-emitting.
- 3) keep high quality,low lighting decay,energy saving.
- 4) with high adjustable brightnessit can fully satisfy various customer requirements.
- 5) synchronously adjust the brightness and color to make the true and exquisite image.

Product Parameters:

Item	Parameter
Unit Module	Model Number
	SF-SS5-8-A
	Module size
	160mm*160mm
	Pixel pitch
	5mm
	Pixels Density
	40000dots/m2
	Pixel configuration
	1R1G1B
	Package mode
	Nationstar SMD2727
	Pixel resolution
	32dots(W)*32dots(H)
Cabinet	Max Power
	25W
	Module thickness
	22mm
	Weight
	0.37kg
	Drive type
	Constant drive
	Scan mode
	1/8
	Port type
	HUB75-A
	Brightness of white balance
	≥5500 6000cd/m2
Power	Dimension
	960mm*960mm*100 mm
	Monomer Module Number
	36pcs
	Power supply
	5V/40A*6 pcs
	Thermal discharge
	fan 2pcs
	Pixel per cabinet
	96mm*96mm
Control system	Best viewing distance
	5M 15M
	viewing angle
	120°(W) 110°(H)
Main technical parameter	Temperature
	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity
	10%-95%
Power	Thickness
	122mm
	Working voltage
	AC220V±10%
Control system	Average Power consumption
	350W/
	Max.Power consumption
	≤1100W/
Main technical parameter	Current
	≤20mA(single LED)
	CPU
	Pentium4 or above P4 or can more
Main technical parameter	Operation system
	WIN98/2000/NT/XP/WIN7
	Control method
	Synchronization
Main technical parameter	Driving device
	Constant drive IC
	Refresh frequency
	≥1920HZ
Main technical parameter	Grey scale/colors
	4096gray level/16.7M colors
	MTBF
	≥100000hours
Main technical parameter	Power switch
	Automatic switch

Advantage:

- 1.simple structure in linear type ,easy in installation and maintation.
- 2.widely used in advertising, sports, industrial enterprises, transportation, stations, terminals, airports, construction, education system and other public places
- 3.strictly quality control and testing.
- 4.suppooort point-to-point correction function, the consistency of the color and the brightness in the process of using.
- 5.with the high quality raw material/mature craft scale production,the quality guaranteed.

Project Show:



**SOL COLUR** SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen