



Lightweight P8 Outdoor Led Screen Exterior Led Display Easy To Maintain

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: IP65, CE, EMC
- Model Number: P8
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE, FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320mm*160mm
- Pixel Pitch: 8mm
- Pixel Configuration: 1R1G1B
- Max Power: 25W
- Weight: 0.37kg
- Highlight: **Lightweight P8 Outdoor Led Screen, Exterior Led Display Easy To Maintain, Lightweight Exterior Led Display**



for more products please visit us on sol-colur.com

Product Description

Pixel Pitch 8mm Outdoor Advertising LED Display Brightness 4800-5500 Easy To Maintain

Product Description

1. Nice appearance and simple structures.
2. Lightweight. Convenient in transporting and installing & saving labor cost, suitable for flow shows.
3. Humanized operating interface with breakdown indicator lights, easy to maintain.
4. High debugging brightness and no damage to gray scale, achieving the debugging technology for nice image.

P8 technology parameters

	Item	Parameter
Unit Module	Model Number	SF-SS8-4-A
	Module size	320mm*160mm
	Pixel pitch	8mm
	Pixels Density	15625dots/m2
	Pixel configuration	1R1G1B
	Package mode	SMD2727
	Pixel resolution	40dots(W)*20dots(H)
	Max Power	25W
	Module thickness	22mm
	Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6200 6500cd/m2
LED Cabinet	Dimension	1024mm*768mm*100 mm
	Monomer Module Number	24pcs
	Power supply	5V/40A*4pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	128mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	330W/
	Max Power consumption	≤1100W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1920HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥100000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

Product Features:

1. Can play different formats of image files, flash, WAV/MIDI, video signal from TV, video signal from video and other equipment.
2. With good lightening accordance and no mosaic.
3. Different video frequency can be changed freely at the same time, and the image.
4. usually use for advertising outdoor.
5. High brightness, and can be adjustable, meets the need of changing requirement.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen