



## Lightweight 5mm Indoor LED Video Wall 40000 Dots / M2 Pixels Density 25W

### Our Product Introduction

#### Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: IP65, FCC, CCC
- Model Number: P5
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



#### Product Specification

- Module Size: 320mm\*160mm
- Pixel Pitch: 5mm
- Scan Mode: 1/16
- Weight: 0.21kg
- Max Power: 25W
- Highlight: Lightweight Indoor LED Video Wall, light weight led display 25W, 5mm Indoor LED Video Wall



## Product Description

Lightweight Indoor Full Color LED Display 40000 Dots / M2 Pixels Density 25W Power

### Product Description

1. High debugging brightness and no damage to gray scale, achieving the debugging technology for nice image.
2. Lightweight. Convenient in transporting and installing & saving labor cost, suitable for flow shows.
3. Nice appearance and simple structures.
4. Jointed correctly, being installed & dismounted by one person without tool.
5. Humanized operating interface with breakdown indicator lights, easy to maintain.

### P5 Indoor technology parameters

	Item	Parameter
Unit Module	Model Number	SF-TS5.0-16S-A
	Module size	320mm*160mm
	Pixel pitch	5mm
	Pixels Density	40000 dots /m2
	Pixel configuration	1R1G1B
	Package mode	SMD2121
	Pixel resolution	32dots(W)*32dots(H)
	Max Power	25W
	Module thickness	14.27mm
	Weight	0.21kg
	Drive type	Constant drive
	Scan mode	1/16
	Port type	HUB75-A
	Brightness of white balance	≥1600cd/m2
LED Cabinet	Dimension	640mm*640mm*
	Monomer Module Number	16pcs
	Power supply	5V/40A*2PCS
	Thermal discharge	fan 2pcs
	Pixel per cabinet	128mm*128mm
	Best viewing distance	5M 30M
	Best viewing angle	110°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
Power	Thickness	85mm
	Working voltage	AC220V±10%
	Average Power consumption	500W/
	Max Power consumption	≤1180W/
Control system	Current	≤20mA(single LED)
	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
Main technical parameter	Control method	Synchronization
	Driving device	Constant drive IC
	Refresh frequency	≥1080HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch

### Products Feature

1. Wide viewing angle: Horizontal & vertical viewing angles are wide, suit to environment of wide Horizontal.
2. Energy saving & environment protection, antistatic, dust-proof, good heat dissipation, cost-effective .
3. Brightness can be adjustable to meet the need of changing requirement of customer in environment.
4. Module dot individually, it can fix easily without affecting others.
5. Working with control card and power supply, LED Display could show a variety of video, animation, graphic and so on.

### Project Show:



**SOL COLUR**  **SHENZHEN SOL COLUR DISPLAY CO.,LTD**

 +86 13751136904

 [chenhao@sol-colour.com](mailto:chenhao@sol-colour.com)

 [sol-colour.com](http://sol-colour.com)

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen