



Lightweight 5mm Led Display 1/16 Scan Mode Advertising Led Video Wall

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: IP65, CE, RoHS
- Model Number: P5
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE, FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320mm*160mm
- Pixel Pitch: 5mm
- Scan Mode: 1/16
- Weight: 0.21kg
- Pixel Resolution: 32dots(W)*32dots(H)
- Pixel Configuration: 1R1G1B
- Highlight: **Lightweight 5mm Led Display ,
1/16 Scan advertising led video wall ,
light weight led display 1/16 Scan**

Product Description

Pixel Pitch 5mm Indoor Led Display Screen 1/16 Scan Mode Module Size 320mm*160mm

Product Description

1. Constant current chip driving reduces the power consumption and prompts the stability, Simple modular design is low cost and easy to maintain.
2. Can undertake single point, single lamp maintenance, the cost is low.
3. Besides, high definition effect comes with uniform luminance and soft color is suitable for indoor close range viewing.
4. Neat appearance, light weight, small size and safe.

P5 Indoor technology parameters

| Item | Parameter |
|--------------------------|-----------------------------|
| Unit Module | Model Number |
| | SF-TS5.0-16S-A |
| | Module size |
| | 320mm*160mm |
| | Pixel pitch |
| | 5mm |
| | Pixels Density |
| | 40000 dots /m2 |
| | Pixel configuration |
| | 1R1G1B |
| | Package mode |
| | SMD2121 |
| | Pixel resolution |
| | 32dots(W)*32dots(H) |
| LED Cabinet | Max Power |
| | 25W |
| | Module thickness |
| | 14.27mm |
| | Weight |
| | 0.21kg |
| | Drive type |
| | Constant drive |
| | Scan mode |
| | 1/16 |
| | Port type |
| | HUB75-A |
| | Brightness of white balance |
| | ≥1600cd/m2 |
| Power | Dimension |
| | 640mm*640mm* |
| | Monomer Module Number |
| | 16pcs |
| | Power supply |
| | 5V/40A*2PCS |
| | Thermal discharge |
| | fan 2pcs |
| | Pixel per cabinet |
| | 128mm*128mm |
| Control system | Best viewing distance |
| | 5M 30M |
| | Best viewing angle |
| | 110°(W) 110°(H) |
| | Temperature |
| | storage:-35°C +85°C |
| | working:-20°C +50°C |
| | Relative humidity |
| | 10%-95% |
| | Thickness |
| Main technical parameter | 85mm |
| | Working voltage |
| | AC220V±10% |
| | Average Power consumption |
| | 500W/ |
| | Max Power consumption |
| | ≤1180W/ |
| | Current |
| | ≤20mA(single LED) |
| | CPU |
| Main technical parameter | Pentium4 or above P4 |
| | Operation system |
| | WIN98/2000/NT/XP/WIN7 |
| | Control method |
| | Synchronization |
| Main technical parameter | Driving device |
| | Constant drive IC |
| | Refresh frequency |
| | ≥1080HZ |
| | Grey scale/colors |
| Main technical parameter | 4096gray level/16.7M colors |
| | MTBF |
| | ≥9000hours |
| Main technical parameter | Power switch |
| | Automatic switch |

Products Feature

1. Ultra thin, super light design, easy and fast to assemble and disassemble.
2. High refresh rate, HD video with vivid pictures.
3. Higher precision and seamless connection.
4. Tidy and beautiful, good heat dissipation.
5. Higher precision and seamless connection.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen