



4mm Pixel Pitch HD Led Backdrop Screen Rental , Led Stage Curtain Screen SMD2121

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: sol colur
- Certification: FCC Rosh IP65
- Model Number: p4
- Minimum Order Quantity: 1pieces
- Price: Negotiable
- Packaging Details: Flight Case , Wooden Box , Carton
- Delivery Time: 15-20days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meters/ per month



Product Specification

- Product Name: P4
- Pixel Pitch: 4mm
- Weight: 0.28kg
- Scan Mode: 32S
- Control Method: Synchronization
- Highlight: **SMD2121 Led Backdrop Screen,
HD Led Backdrop Screen,
4mm Pixel Pitch Led Backdrop Screen**



Product Description

Indoor 4mm HD indoor SMD2121 full color p4 p5 p6 rental led display screen

Detailed Product Description:

Module size:	256*128mm	Brightness:	900-1200nits
Control method:	Synchronization	Color:	1R1G1B
Module number:	Indoor P	Package mode:	Nationstar SMD 2121
Warranty:	2 Years	Pixel resolution:	64dots(W)*32dots(H)

Product Parameters:

	Item	Parameter
Unit Module	Model Number	SF-TS4.0-16S-A
	Module size	256mm*128mm
	Pixel pitch	4mm
	Pixels Density	62500dots/m2
	Pixel configuration	1R1G1B
	Package mode	Nationstar SMD2121
	Pixel resolution	64dots(W)*32dots(H)
	Max Power	18W
	Module thickness	26mm
	Weight	0.28kg
	Drive type	Constant drive
	Scan mode	32S
	Port type	HUB75-A
	Brightness of white balance	≥1500cd/m2
LED Cabinet	Dimension	512mm*512mm*
	Monomer Module Number	16pcs
	Power supply	5V/40A*2pc
	Thermal discharge	fan2pcs
	Pixel per cabinet	128mm*128mm
	Best viewing distance	4M 20M
	Best viewing angle	110°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
Power	Thickness	85mm
	Working voltage	AC220V±10%
	Average Power consumption	580W/
	Max.Power consumption	≤1000W/
Control system	Current	≤20mA(single LED)
	CPU	Pentium4 or above P4 or more
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1080HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch

Advantage:

1. High brightness and color uniformity
2. Excellent flatness and no splicing gap between modules
3. low gray level and high expressive ability, rich program level and obvious synchronization with computer.
4. High definition and adjustable, which can display DVD, VCR, TV and dynamic images.
5. Gratifying is that mosaics can be solved with consistency of light.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen