



## High Uniformity 10mm HD Outdoor Fixed LED Display 22mm Thickness

### Our Product Introduction

#### Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: FCC, RoHS, CE
- Model Number: P10
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE, FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



#### Product Specification

- Module Size: 320mm\*160mm
- Color: Black
- Pixel Pitch: 10mm
- Weight: 0.37kg
- Scan Mode: 1/4
- Module Thickness: 22mm
- Highlight: Outdoor Fixed LED Display 22mm Thickness, High Uniformity Outdoor Fixed LED Display, High Uniformity 10mm LED Display

for more products please visit us on [sol-colur.com](http://sol-colur.com)

## Product Description

Pixel Pitch 10mm HD LED Screen Brightness 4500-5500 Scan Mode 1/4 Energy Saving

### Product Description

1. Energy saving design and good performance in color uniformity.
2. High brightness meet the needs of various application environments.
3. Excellent visual effect, better viewing effect for text and graphic or video.
4. Fit for the outdoor fixed commercial applications such as shopping mall, mobile truck ,single/double pole mounted ,wall mounted.
5. Environmental raw material.

### P10 outdoor technology parameters

	Item	Parameter
sUnit Module	Model Number	SF-SS10-4S-A
	Module size	320mm*160mm
	Pixel pitch	10mm
	Pixels Density	10000dots/m2
	Pixel configuration	1R1G1B
	Package mode	SMD3535
	Pixel resolution	32dots(W)*16dots(H)
	Max Power	35W
	Module thickness	22mm
	Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6800 7200cd/m2
LED Cabinet	Dimension	960mm*960mm*100 mm
	Monomer Module Number	18pcs
	Power supply	5V/40A*4pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	96mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	180W/
	Max Power consumption	≤480W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1200HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

### Features:

1. IS table cabinet, stronger without distortion, anti-rust.
2. High Brightness and Refresh Rate.
3. Energy Saving.
4. High Uniformity & Contrast.
5. Efficient After-sales.
- 6 Low consumption, stable performance, highly durable.

### Project Show:



**SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD**



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen