



P4 Outdoor Led Stage Display Screen , Led Video Display Panels High Resolution

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: sol colur
- Certification: FCC Rosh 3C
- Model Number: p4
- Minimum Order Quantity: 1pieces
- Price: Negotiable
- Packaging Details: Flight Case , Wooden Box , Carton
- Delivery Time: 15-20days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meters/ per month



Product Specification

- Product Name: P4
- Pixel Pitch: 4mm
- Weight: 0.21kg
- Brightness: 5000-5500
- Scan Mode: 10S
- Highlight: **P4 Outdoor Led Stage Display Screen ,
Led Video Display Panels High Resolution**

for more products please visit us on sol-colur.com

Product Description

High resolution P4 outdoor stage led display/advertising led video wall / led screen

Detailed Product Description:

Module size:	256*128 mm	Brightness:	5000-5500nits
Control method:	Synchronization	Color:	1R1G1B
Module number:	Outdoor P4	Package mode:	Nationstar SMD1921
Warranty:	2 Years	Pixel resolution:	64dots(W)*32dots(H)

Product Parameters:

	Item	Parameter
Unit Module	Model Number	SF-SS4-8-A
	Module size	256mm*128mm
	Pixel pitch	4mm
	Pixels Density	62500dots/m2
	Pixel configuration	1R1G1B
	Package mode	Nationstar SMD1921
	Pixel resolution	64dots(W)*32dots(H)
	Max Power	27.5W
	Module thickness	22mm
	Weight	037kg
	Drive type	Constant drive
	Scan mode	1/8
	Port type	HUB75-A
	Brightness of white balance	≥6000~6500cd/m2
LED Cabinet	Dimension	1024mm*768mm*100mm
	Monomer Module Number	24pcs
	Power supply	5V/40A*4pc
	Thermal discharge	fan 2pcs
	Pixel per cabinet	256mm*128mm
	Best viewing distance	6M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
Power	Thickness	122mm
	Working voltage	AC220V±10%
	Average Power consumption	330W/
	Max.Power consumption	≤1100W/
Control system	Current	≤20mA(single LED)
	CPU	Pentium4 or above P4 or more
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1920HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥100000hours
	Power switch	Automatic switch

Advantage:

1. Multiple waterproof casing design, single box full inspection factory, the protection level IP65 mature signal transmission architecture, equipped with the upgraded version of power management technology, the use of more secure and reliable.
2. Classic module design, superior product performance, stability.
3. New perspective optimization design, covering the mainstream audience.
4. Uniform color, high contrast, beautiful natural picture.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen