



## Pixel Pitch 6mm Led Display Outdoor Led Display Advertising Board Max Power 25W

### Our Product Introduction

for more products please visit us on [sol-colur.com](http://sol-colur.com)

#### Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: IP65, EMC, FCC
- Model Number: P6
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE, FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



#### Product Specification

- Module Size: 320\*160mm
- Max Power: 25W
- Scan Mode: 1/8
- Pixel Configuration: 1R1G1B
- Weight: 0.38kg
- Highlight: Pixel Pitch 6mm Led Display, 25W outdoor led display advertising board, 6mm Outdoor Led Display Advertising Board



#### More Images



## Product Description

Pixel Pitch 6mm SMD Outdoor Led Display Module Size 320mm\*160mm Max Power 25W

### Product Description

1. Waterproof IP65 rating, guaranteeing our product's stable broadcasting in harshest weather condition.
2. Able to show a variety of content of video, animation, graphic and so on.
3. Strict system control and pixel to pixel correction make the image smooth and uniformity.
4. Module design makes module individual and can fix easily without affecting others.

P6 outdoor full-color technology parameters

	Item	Parameter
Unit Module	Model Number	SF-SS6-8-A
	Module size	320mm*160mm
	Pixel pitch	6mm
	Pixels Density	27777 dots /m2
	Pixel configuration	1R1G1B
	Package mode	SMD2727
	Pixel resolution	54dots(W)*27dots(H)
	Max Power	25W
	Module thickness	17.5mm
	Weight	0.38kg
	Drive type	Constant drive
	Scan mode	1/8
	Port type	HUB75-B
	Brightness of white balance	≥6000 6500cd/m2
LED Cabinet	Dimension	960mm*960mm*100 mm
	Monomer Module Number	25pcs
	Power supply	5V/40A*5pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	96mm*96mm
	Best viewing distance	6M 30M
	Best viewing angle	120°(W)110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
Power	Thickness	122mm
	Working voltage	AC220V±10%
	Average Power consumption	400W/
	Max Power consumption	≤1200W/
Control system	Current	≤20mA(single LED)
	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
Main technical parameter	Control method	Synchronization
	Driving device	Constant drive IC
	Refresh frequency	≥1920HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

### Product features

1. After a dustproof and waterproof tested to reach its target IP65.
2. Large viewing angle and smooth displaying provide excellent visual effect from every angle.
3. High quality LED chip and high anti-static electricity capacity.
4. Ultra-high brightness, low attenuation, high reliability and weather ability.
5. Widely used in advertising, sports, industrial enterprises, transportation, stations, terminals, airports, construction, education system and other public places.

### Project Show:



**SOL COLUR** SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen