



P4 HD Indoor Rental Led Display , Full Color Large Led Video Screens Constant Drive

Our Product Introduction

for more products please visit us on sol-colur.com

Basic Information

- Place of Origin: SHENZHEN CHINA
- Brand Name: sol colur
- Certification: 3C IP65 FCC
- Model Number: p4
- Minimum Order Quantity: 1pieces
- Price: Negotiable
- Packaging Details: Flight Case , Wooden Box , Carton
- Delivery Time: 15-20days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meters/ per month



Product Specification

- Product Name: P4
- Module Size: 256*128mm
- Pixel Pitch: 4mm
- Resoution: 62500 Dots/m2
- Max Power: 0.37kg
- Highlight: Full Color Indoor Rental Led Display ,
P4 HD Indoor Rental Led Display ,
Constant Drive Indoor Rental Led Display



More Images



Product Description

P4 indoor HD module size 256*128mm full color rental led screen

Detailed Product Description:

Module size:	256*128mm	Brightness:	900-1200
Control Method:	Synchronization	Color:	1R1G1B
Module number:	Indoor P4	Package mode:	NationstarSMD2121
Warranty:	2 Years	Pixel resolution:	64dots(W)*32dots(H)

Product Parameters:

Unit Module	Item	Parameter
	Model Number	SF-TS4.0-16S-A
	Module size	256mm*128mm
	Pixel pitch	4mm
	Pixels Density	62500dots/m2
	Pixel configuration	1R1G1B
	Package mode	NationstarSMD2121
	Pixel resolution	64dots(W)*32dots(H)
	Max Power consumption	18W
	Module thickness	26mm
	Weight	0.28kg
	Drive type	Constant drive
	Scan mode	16S
	Port type	HUB75-A
	Brightness of white balance	≥1500cd/m2
Cabinet	Dimension	512mm*512mm
	Monomer Module Number	16pcs
	Power supply	5V/40A*2pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	128*128mm
	Best viewing distance	4M 20M
	Best viewing distance	110°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	85mm
Power	Working voltage	AC220V±10%
	Average Power consumption	580W/H
	Max.Power consumption	≤1000W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4 or more
	Operation system	WIN98/2000/NT/XP
	Control method	Synchronization
	Driving device	Constant currentdriver IC
	Refresh frequency	≥1080HZ

Main technical parameter	Grey scale/colors	gray4096 levels of each color(RGB)/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch

Advantage:

1. High definition and high resolution
2. Reply enquiries in 12 hours working time
3. RGB each basic color has 16 color change ability
4. Low grayscale and high expression ability, rich program level, synchronous display with computer.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen