



## P3.91 Led Stage Display Screen 1R1G1B Pixel Configuration Module Size 250mm\*250mm

Our Product Introduction

for more products please visit us on [sol-colur.com](http://sol-colur.com)

### Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: IP65, CCC, FCC
- Model Number: P3.91
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month





### Product Specification

- Module Size: 250mm\*250mm
- Pixel Pitch: 3.91mm
- Pixel Configuration: 1R1G1B
- Scan Mode: 1/16
- Weight: 0.58kg
- Highlight: 250mm\*250mm Led Stage Display Screen, P3.91 Led Stage Display Screen



### More Images



## Product Description

### Product Description

1. Ingress protection being IP65, weather proof and dust proof.
2. Outdoor high resolution and high brightness, smallest pixel in the world 3.91mm, unequalled image quality in outdoor environment.
3. Super thin and light with die-casting aluminum cabinet design.
4. High brightness uniformity and color uniformity.
5. Quick installation and removal with facile connection lock.

Item	Parameter	
Pixel pitch	3.91mm	
Module size	250mm*250mm	
Physical density	65536dots/m2	
Pixel configuration	1R1G1B	
Package mode	SMD1921	
Pixel resolution	64dots(W)*64dots(H)	
Max Power	38W	
Module thickness	13.41mm	
Weight	0.58kg	
Drive type	Constant drive	
Scan mode	1/16	
Dimension	500mm*500mm	
Monomer Module Number	4pcs	
Power supply	5V/60A*1pcs	
Thermal discharge	Fan2pcs	
Pixel per cabinet	128*128	
Best viewing distance	10M~30M	
Best viewing angle	110°(W)110°(H)	
Temperature	Storage:-35°C~+85°C Working:-20°C~+50°C	
Relative humidity	10%-95%	
Thickness	100mm	
working voltage	AC220V±10%	
Average Power consumption	200W/	
Max Power consumption	≤400W/	
Current	≤20mA(single LED)	
CPU	Pentium4 or above P4	
Operation system	WIN98/2000NT/XP/WIN7	
Control method	Synchronization	
Driving device	Constant drive IC	
Refresh frequency	≥1200HZ	
Grey scale/colors	4096 levels of each color(RGB)/16.7M colors	
MTBF	≥9000hours	
Power switch	Automatic switch	

### Project Show:



**SOL COLUR**  **SHENZHEN SOL COLUR DISPLAY CO.,LTD**

 +86 13751136904

 [chenhao@sol-colour.com](mailto:chenhao@sol-colour.com)

 [sol-colour.com](http://sol-colour.com)

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen