



## Dustproof 1R1G1B Outdoor Fixed LED Display 35W P10 Weather Resistance

### Our Product Introduction

#### Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: CE, EMC, IP65
- Model Number: P6
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 Days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



#### Product Specification

- Module Size: 320\*160mm
- Pixel Resolution: 32dots(W)\*16dots(H)
- Max Power: 35W
- Pixel Configuration: 1R1G1B
- Module Thickness: 22mm
- Highlight: **dustproof Outdoor Fixed LED Display, Outdoor Fixed LED Display weather resistance, weather resistance P10 LED Display**



## Product Description

1R1G1B Pixel Outdoor Led Advertising Screens , Large Led Display Panels 35W P10

### Product Description

- 1.Outdoor Magnesium alloy Cabinet,so lighter and thinner.
- 2.High quality and Reliable.
- 3.Over years of manufacturing experience.
- 4.2 years warranty, easy to install & maintenance.
- 5.Clear picture without flicker and distortion.
6. Low consumption, stable performance, highly durable.

### P10 outdoor technology parameters

	Item	Parameter
sUnit Module	Model Number	SF-SS10-4S-A
	Module size	320mm*160mm
	Pixel pitch	10mm
	Pixels Density	10000dots/m2
	Pixel configuration	1R1G1B
	Package mode	SMD3535
	Pixel resolution	32dots(W)*16dots(H)
	Max Power	35W
	Module thickness	22mm
	Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6800 7200cd/m2
LED Cabinet	Dimension	960mm*960mm*100 mm
	Monomer Module Number	18pcs
	Power supply	5V/40A*4pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	96mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	180W/
	Max Power consumption	≤480W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1200HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

### Product features

1. High uniformity display color.
2. rich in content: can display text, graphics, images, animation, video information.
3. IP65 grade for high performance waterproof and dustproof capability.
4. High quality LED chip and high anti-static electricity capacity.
5. Ultra-high brightness, low attenuation, high reliability and weather ability.
- 6 excellent viewing angle: both horizontal and vertical have a large viewing angle, which is suitable for environments with wide horizontal distribution and large height difference.

### Project Show:



**SOL COLUR**  **SHENZHEN SOL COLUR DISPLAY CO.,LTD**

 +86 13751136904

 [chenhao@sol-colour.com](mailto:chenhao@sol-colour.com)

 [sol-colour.com](http://sol-colour.com)

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen