

25 Watt Outdoor SMD LED Display 1/4 Scan Mode P8 SMD2727 1R1G1B Pixel Configuration

Our Product Introduction

for more products please visit us on sol-colur.com

Basic Information

- Place of Origin: SHENZHEN,CHINA
- Brand Name: SOL COLUR
- Certification: ROHS,CE,FCC
- Model Number: P8
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320mm*160mm
- Pixel Pitch: 8mm
- Pixel Resolution: 40dots(W)*20dots(H)
- Max Power: 25W
- Scan Mode: 1/4
- Module Weight: 0.37kg
- Highlight: **P8 Outdoor SMD LED Display, 25 Watt Outdoor SMD LED Display**



Product Description

25 Watt Outdoor SMD LED Display 1/4 Scan Mode P8 SMD2727 1R1G1B Pixel Configuration

Product Description

1. Using 1/4 scan drive design, the brightness can reach 6000-6500nits
2. Outlet and air inlet with waterproof cover, waterproof level higher than the general market products.
3. Uniform color and high contrast ratio, bringing up fresh and natureal image.
4. Super wide viewing angle increasing its value by covering more audience.
5. No deformation under sunlight by the use of anti-UV modules.

P8 technology parameters

	Item	Parameter
Unit Module	Model Number	SF-SS8-4-A
	Module size	320mm*160mm
	Pixel pitch	8mm
	Pixels Density	15625dots/m2
	Pixel configuration	1R1G1B
	Package mode	SMD2727
	Pixel resolution	40dots(W)*20dots(H)
	Max Power	25W
	Module thickness	22mm
	Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6200 6500cd/m2
LED Cabinet	Dimension	1024mm*768mm*100 mm
	Monomer Module Number	24pcs
	Power supply	5V/40A*4pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	128mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	122mm
Power	Working voltage	AC220V±10%
	Average Power consumption	330W/
	Max Power consumption	≤1100W/
	Current	≤20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
Main technical parameter	Driving device	Constant drive IC
	Refresh frequency	≥1920HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥100000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

Products Feature

1. High and adjustable brightness can meet the demands of the changing requirement of Customer in different environments.
2. No mosaic due to excellent flatness and nice uniformity of light-emitting.
3. Aluminum cabinet can be used for lower weight.
4. Environmental-friendly and energy-saving.
5. Good heat dissipation capability because of the unique design of vent fan (liking shutter).

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen