



## High Brightness Outdoor Rental LED Display SMD 2727 1/13 Scan Mode 38.5W

### Our Product Introduction

#### Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: CE, IP65, CCC
- Model Number: P4.81
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE, FLIGHT CASE
- Delivery Time: 15-20 Days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



#### Product Specification

- Pixel Pitch: 4.81mm
- Module Size: 250mm\*250mm
- Max Power: 38.5W
- Module Thickness: 20mm
- Weight: 0.58kg
- Scan Mode: 1/13
- Highlight: **Outdoor Rental LED Display,  
SMD 2727 Rental LED Display**

for more products please visit us on [sol-colur.com](http://sol-colur.com)

## Product Description

High Brightness Outdoor Rental LED Display SMD 2727 1/13 Scan Mode 38.5W

### Product Description

- 1.High brightness Contrast:4000:1, which is a very high level to ensure a vivid image of our LED display screen system
2. First-class LED chip to ensure the long lift-time and high brightness of our LED display screen system
- 3.Clear vivid image quality even in direct, full-on sunlight to ensure you attracts more audience
- 4.Long-term Brightness:More 7000-nit brightness(for outdoor full color)(2000 nits brightness for indoor full color)capacity throughout product lifetime of the LED display screen.
- 5.Easy Installation & Using: easy & simple installation interface and user friendly software to ensure the user friendly interface of the LED display screen system
- 6.Convenient Servicing: Front and rear cabinet access make the maintance work very convenient and low cost.

### OUTDOOR P4.81 SMD 3IN1 TECHNICAL PARAMETERS

	Item	Parameter
	Model Number	SF-SS4.81-13S-A
Unit Module	Module size	250mm*250mm
	Pixel pitch	4.81mm
	Pixels Density	43264 dot/m2
	Pixel configuration	1R1G1B
	Package mode	Nationstar SMD2727
	Pixel resolution	52dots(W)*52 dots (H)
	Max Power	38.5W
	Weight	0.58kg
	Drive type	Constant drive
	Scan mode	1/13
	Port type	HUB75-A
	Brightness of white balance	≥4850cd/m2
LED Cabinet	Dimension	500mm*500mm
	Monomer Module Number	4pcs
	Power supply	5V/60A*1pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	104mm*104mm
	Best viewing distance	2M 14M
	Best viewing angle	110°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
	Thickness	100mm
ower	Working voltage	AC110 220V±10%
	Average Power consumption	200W/
	Max Power consumption	<400W/
	Current	<20mA(single LED)
Control system	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
	Control method	Synchronization
	Driving device	Constant drive IC
	Refresh frequency	>1920HZ

Main technical parameter	Grey scale/colors	16384gray level/16.7M colors
	MTBF	>9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

**Features:**

- 1.High brightness and definition, energy-saving, environment friendly
2. The display adopts high refresh rate, no highlights, perfectly meet the requirements of video image
3. Excellent visual effect, better viewing effect for text and graphic or video.
4. Easy operation and control, simple installation and maintainence.
5. Long lifespan up to 9,000 hours.

**Project Show:**



**SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD**

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen