




Pixel Pitch 4mm Outdoor Advertising LED Display 1/8 Scan Mode 27.5W 1R1G1B

Our Product Introduction


Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: CE, CCC, IP65
- Model Number: P4
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, , Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320*160
- Pixel Pitch: 4mm
- Max Power: 27.5W
- Weight: 0.37kg
- Scan Mode: 1/8
- Module Thickness: 22mm
- Highlight: 27.5W Outdoor Advertising LED Display, 1R1G1B Outdoor Advertising LED Display



Product Description

Pixel Pitch 4mm Outdoor Advertising LED Display 1/8 Scan Mode Module Size 320*160

Product Description

1. Application: Outdoor media, advertising, billboard, sports scoreboard, etc.
2. Installation : Wall-mounted, Standing pillar, Building roof.
3. Control: by computer and software ;.
4. Connection : Connected to computer for signal, and to power box for electricity.
5. Maintenance: Rear service, easy replacement with enough spare parts.

SC outdoor full-color technology parameters

SC outdoor full-color technology parameters

	Item	Parameter
Unit Module	Model Number	SC-P4(1921) 80*40-4L 10S-V1.6
	Module size	320mm*160mm
	Pixel pitch	4mm
	Pixels Density	62500dot/m2
	Pixel configuration	1R1G1B
	Package mode	SMD1921
	Pixel resolution	80dots(W)*40dots(H)
	Max Power	33W
	Module thickness	16mm
	Weight	0.58kg
	Drive type	Constant drive
	Scan mode	1/10
	Port type	HUB75
	Brightness of white balance	≥6000 6500cd/m2
LED Cabinet	Dimension	960*960
	Monomer Module Number	18pcs
	Power supply	5V/60A*3 pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	960mm*960mm
	Best viewing distance	4M 10M
	Best viewing angle	110°(W) 110°(H)
	Temperature	working:-20℃ +50℃
	Relative humidity	10%-95%
Power	Thickness	100mm
	Working voltage	AC220V±10%
	Average Power consumption	325W/
	Max .Power consumption	≤975W/
Control system	Current	≤20mA(single LED)
	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
Main technical parameter	Control method	Synchronization
	Driving device	Constant drive IC
	Refresh frequency	≥1920HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥100000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

Product Features:

- 1, IP65 weather rating, ensures great quality outputs in every condition.
- 2, Good heat dissipation, with special fans ventilation design.
- 3, High fresh rate up to 1,920Hz, high contrast ration 4,000:1, vivid color.
- 4, SMD LEDs ensure large viewing angle, up to 110° horizontally and 110° vertically. Image no distortion, no color cast in any angle within this range, reaches to more audiences.
- 5, 4mm high definition for outdoor advertising use, clear performance.



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colour.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen