



Pixel Pitch 10mm SMD Outdoor Led Display 35W Large Viewing Angle 1/4 Scan Mode

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: CCC, IP65, CE
- Model Number: P10
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320mm*160mm
- Scan Mode: 1/4
- Pixel Configuration: 1R1G1B
- Module Thickness: 22mm
- Pixel Pitch: 10mm
- Pixel Resolution: 32dots*16dots
- Highlight: 10mm Outdoor Led Display, 35W Outdoor Led Display



Product Description

Pixel Pitch 10mm SMD Outdoor Led Display 35W Large Viewing Angle 1/4 Scan Mode

Product Description

1. Waterproof Outdoor IP65 Cabinet size can be Customized as your LED Display Size.
2. personalized and complete solution for your requiremen
3. Wide Viewing angle can attract more passersby's attentions.
4. factory price and good quality
5. The led display is set vertically and the inclination angle are adjustable for the best possible viewing angle and camera shooting angles.

P10 outdoor technology parameters

Item	Parameter
sUnit Module	Model Number
	SF-SS10-4S-A
	Module size
	320mm*160mm
	Pixel pitch
	10mm
	Pixels Density
	10000dots/m2
	Pixel configuration
	1R1G1B
	Package mode
	SMD3535
	Pixel resolution
	32dots(W)*16dots(H)
LED Cabinet	Max Power
	35W
	Module thickness
	22mm
	Weight
	0.37kg
	Drive type
	Constant drive
	Scan mode
	1/4
	Port type
	HUB75-A
	Brightness of white balance
	≥6800 7200cd/m2
LED Cabinet	Dimension
	960mm*960mm*100 mm
	Monomer Module Number
	18pcs
	Power supply
	5V/40A*4pcs
	Thermal discharge
	fan 2pcs
	Pixel per cabinet
	96mm*96mm
Power	Best viewing distance
	8M 15M
	Best viewing angle
	120°(W) 110°(H)
	Temperature
Power	storage:-35°C +85°C
	working:-20°C +50°C
	Relative humidity
	10%-95%
	Thickness
Power	122mm
	Working voltage
	AC220V±10%
	Average Power consumption
	180W/
Control system	Max Power consumption
	≤480W/
	Current
	≤20mA(single LED)
	CPU
Main technical parameter	Pentium4 or above P4
	Operation system
	WIN98/2000/NT/XP/WIN7
	Control method
	Synchronization
Main technical parameter	Driving device
	Constant drive IC
	Refresh frequency
	≥1920HZ
	Grey scale/colors
	4096gray level/16.7M colors
Main technical parameter	MTBF
	≥9000hours
	Power switch
Main technical parameter	Automatic switch
	Display Mode
	≥800*600/1024*768

Features:

1. The brightness can be adjusted automatically as the environmental changes;
2. The angle of the ground support structure can be adjusted as you need, to suit the best viewing angle for audience and cameras
3. Excellent service including free technical support when in the warranty
4. Based on CE, FCC, ROHS Certification.
5. Energy saving and noiseless power supply, excellent heat dissipation to ensure power supply and life span.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen