



Energy Efficient Outdoor Fixed LED Display 35W 1/4 Scan Mode Constant Drive

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: CE, IP65, EMC
- Model Number: P10
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320mm*160mm
- Max Power: 35W
- Module Weight: 0.37kg
- Scan Mode: 1/4
- Pixel Configuration: 1R1G1B
- Module Thickness: 22mm
- Highlight: Outdoor Fixed LED Display Constant Drive, Energy Efficient Outdoor Fixed LED Display, Energy Efficient Outdoor Fixed LED screen



Product Description

Energy Saving P10 Outdoor Advertising LED Display 35W 1/4 Scan Mode Constant Drive

Product Description

LED display, also called led screen, led video wall, or led sign, with its unique advantages, has gradually replaced the traditional billboards, light boxes, etc. LED display advertising has become a new force in the media industry.

Traditional advertising can only show pictures, But LED display/led video wall/led screen can perfect combine text, pictures, video, and sound with high resolution, high brightness and full colour!

LED display Advertising screen can easily attract the attention of pedestrians, and also are easy to remember, which can generate greater advertising effectiveness. Led display screen now are widely applied in media advertising, transportation, Security, Real estate and Stage show background.

P10 outdoor technology parameters

	Item	Parameter
sUnit Module	Model Number	SF-SS10-4S-A
	Module size	320mm*160mm
	Pixel pitch	10mm
	Pixels Density	10000dots/m2
	Pixel configuration	1R1G1B
	Package mode	SMD3535
	Pixel resolution	32dots(W)*16dots(H)
	Max Power	35W
	Module thickness	22mm
	Weight	0.37kg
	Drive type	Constant drive
	Scan mode	1/4
	Port type	HUB75-A
	Brightness of white balance	≥6800 7200cd/m2
LED Cabinet	Dimension	960mm*960mm*100 mm
	Monomer Module Number	18pcs
	Power supply	5V/40A*4pcs
	Thermal discharge	fan 2pcs
	Pixel per cabinet	96mm*96mm
	Best viewing distance	8M 15M
	Best viewing angle	120°(W) 110°(H)
	Temperature	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity	10%-95%
Power	Thickness	122mm
	Working voltage	AC220V±10%
	Average Power consumption	180W/
	Max Power consumption	≤480W/
Control system	Current	≤20mA(single LED)
	CPU	Pentium4 or above P4
	Operation system	WIN98/2000/NT/XP/WIN7
Main technical parameter	Control method	Synchronization
	Driving device	Constant drive IC
	Refresh frequency	≥1920HZ
	Grey scale/colors	4096gray level/16.7M colors
	MTBF	≥9000hours
	Power switch	Automatic switch
	Display Mode	≥800*600/1024*768

Features:

1. Screen can work under very strong sunlight.
2. Super flatness & uniformity, large viewing angle, high brightness.
3. Excellent service including free technical support when in the warranty
4. Based on CE, FCC, ROHS Certification.
5. Energy saving and noiseless power supply, excellent heat dissipation to ensure power supply and life span.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen