



IP65 LED Outdoor Advertising Screens P4mm SMD1921 Module Size 320*160mm

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: ROHS, EMC, IP65
- Model Number: P4
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, , Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Module Size: 320*160
- Pixel Pitch: 4mm
- Max Power: 27.5W
- Weight: 0.37kg
- Scan Mode: 1/8
- Module Thickness: 22mm
- Highlight: LED Outdoor Advertising Screens P4mm, SMD1921 LED Outdoor Advertising Screens, SMD1921 outdoor video advertising screen



for more products please visit us on sol-colur.com

Product Description

IP65 Outdoor Advertising LED Display Pixel Pitch 4mm SMD1921 Module Size 320*160

Product Description

- 1.Outdoor high resolution and high brightness.
- 2.Ingress protection being IP65, weather proof and dust proof.
- 3.High brightness uniformity and color uniformity.
4. Excellent flatness and no splicing gap between modules.
5. Quick installation and removal with facile connection lock

SC outdoor full-color technology parameters

| | Item | Parameter |
|--------------------------|-----------------------------|-------------------------------|
| Unit Module | Model Number | SC-P4(1921) 80*40-4L 10S-V1.6 |
| | Module size | 320mm*160mm |
| | Pixel pitch | 4mm |
| | Pixels Density | 62500dot/m2 |
| | Pixel configuration | 1R1G1B |
| | Package mode | SMD1921 |
| | Pixel resolution | 80dots(W)*40dots(H) |
| | Max Power | 27.5W |
| | Module thickness | 16mm |
| | Weight | 0.58kg |
| | Drive type | Constant drive |
| | Scan mode | 1/10 |
| | Port type | HUB75 |
| | Brightness of white balance | ≥6000 6500cd/m2 |
| LED Cabinet | Dimension | 960*960 |
| | Monomer Module Number | 18pcs |
| | Power supply | 5V/60A*3 pcs |
| | Thermal discharge | fan 2pcs |
| | Pixel per cabinet | 960mm*960mm |
| | Best viewing distance | 4M 10M |
| | Best viewing angle | 110°(W) 110°(H) |
| | Temperature | working:-20℃ +50℃ |
| Power | Relative humidity | 10%-95% |
| | Thickness | 100mm |
| | Working voltage | AC220V±10% |
| | Average Power consumption | 325W/ |
| Control system | Max .Power consumption | ≤975W/ |
| | Current | ≤20mA(single LED) |
| | CPU | Pentium4 or above P4 |
| Main technical parameter | Operation system | WIN98/2000/NT/XP/WIN7 |
| | Control method | Synchronization |
| | Driving device | Constant drive IC |
| | Refresh frequency | ≥1920HZ |
| | Grey scale/colors | 4096gray level/16.7M colors |
| | MTBF | ≥100000hours |
| | Power switch | Automatic switch |
| | Display Mode | ≥800*600/1024*768 |

Product Features:

- 1, IP65 weather rating, ensures great quality outputs in every condition.
 - 2,Wide color range, excellent color uniformity
 - 3, Stable performance:superior anti UV, sulfide resistant ability, can be long-term used in outdoor
 - 4, SMD LEDs ensure large viewing angle, up to 110° horizontally and 110° vertically.
- Image no distortion, no color cast in any angle within this range, reaches to more audiences.
- 5, Three anti-protection: anti-corrosion, anti-static, moisture, shock, greatly improving the reliability of the product.
 - 6.Perfect uniformity and no mosaic.

Project Show:



SOL COLUR  **SHENZHEN SOL COLUR DISPLAY CO.,LTD**



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen