



## Full Color Outdoor Fixed LED Display P5 HD Module Size 320\*160mm 25 Watt

### Our Product Introduction

#### Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: CE, EMC, IP65
- Model Number: P5
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



#### Product Specification

- Pixel Pitch: 5mm
- Module Size: 320mm\*160mm
- Pixel Configuration: 1R1G1B
- Max Power: 25W
- Weight: 0.37kg
- Scan Mode: 1/8
- Highlight: Outdoor Fixed LED Display 25 Watt, 25 Watt p5 outdoor led display, Outdoor Fixed LED Display P5



## Product Description

Full Color Outdoor Advertising LED Display P5 25W HD Module Size 320\*160 25 Watt

### Product description

- 1.Application: Outdoor media, advertising, billboard.
- 2.Installation : Wall-mounted, Standing pillar, Building roof.
- 3Control: Contolled by computer and software supplied;.
- 4.Certification: CE, FCC, ROHS
- 5.Connection : Connected to computer for signal, and to power box for electricity.

P5 outdoor full-color technology parameters

Item	Parameter
Unit Module	Model Number
	SF-SS5-8-A
	Module size
	320mm*160mm
	Pixel pitch
	5mm
	Pixels Density
	40000dots/m2
	Pixel configuration
	1R1G1B
	Package mode
	SMD2727
	Pixel resolution
	64dots(W)*32dots(H)
LED Cabinet	Max Power
	25W
	Module thickness
	22mm
	Weight
	0.37kg
	Drive type
	Constant drive
	Scan mode
	1/8
	Port type
	HUB75-A
	Brightness of white balance
	≥5500 6000cd/m2
Power	Dimension
	960mm*960mm*100 mm
	Monomer Module Number
	36pcs
	Power supply
	5V/40A*6pcs
	Thermal discharge
	fan 2pcs
	Pixel per cabinet
	96mm*96mm
Control system	Best viewing distance
	5M 15M
	Best viewing angle
	120°(W) 110°(H)
	Temperature
Main technical parameter	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity
	10%-95%
	Thickness
	122mm
Power	Working voltage
	AC220V±10%
	Average Power consumption
	350W/
Control system	Max Power consumption
	≤1200W/
	Current
	≤20mA(single LED)
Control system	CPU
	Pentium4 or above P4
	Operation system
Main technical parameter	WIN98/2000/NT/XP/WIN7
	Control method
	Synchronization
Main technical parameter	Driving device
	Constant drive IC
	Refresh frequency
	≥1920HZ
	Grey scale/colors
	4096gray level/16.7M colors
Main technical parameter	MTBF
	≥10000hours
	Power switch
Main technical parameter	Automatic switch
	Display Mode
	≥800*600/1024*768

### Features:

- 1.Outdoor high resolution 27,777 pixels per square meter for high image quality.
- 2,P5 outdoor led display Stable performance reduces less issues and saving maintenance time and cost.
- 3, SMD LED technolgoy makes video and image quality better effect.
- 4, Energy saving: low electric current, high-bright.
- 5, Super high brightness 6000nits makes led screen still be very clear under the sunshine.
- 6, LED Display can be splicing to several parts and play its information sepatately.

### Project Show:



**SOL COLUR** SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,  
Shenzhen