



SMD3535 HD Outdoor Advertising Led Display Full Color Led Video Billboards P5

Our Product Introduction

Basic Information

- Place of Origin: SHENZHEN, CHINA
- Brand Name: SOL COLUR
- Certification: CE, EMC, IP65
- Model Number: P5
- Minimum Order Quantity: 1 Square Meters
- Price: Negotiable
- Packaging Details: CARTON, WOODEN CASE FLIGHT CASE
- Delivery Time: 15-20 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Pixel Pitch: 5mm
- Module Size: 320mm*160mm
- Pixel Configuration: 1R1G1B
- Max Power: 25W
- Weight: 0.37kg
- Scan Mode: 1/8
- Highlight: SMD3535 Outdoor Advertising Led Display, Led Video Billboards P5, SMD3535 Led Video Billboards



Product Description

SMD3535 HD Advertising Led Display Screen , Full Color Led Video Billboards P5

Product Description

- 1.High brightness,brightness can be customized and adjusted by customer according to customer requirement.
- 2.Wide viewing degree and good vision.
- 3.Packed in fly case which is good for transportation.
- 4.Certification: CE, FCC, ROHS
- 5.save cost for control system and packing charges,freight.

P5 outdoor full-color technology parameters

Item	Parameter
Unit Module	Model Number
	SF-SS5-8-A
	Module size
	320mm*160mm
	Pixel pitch
	5mm
	Pixels Density
	40000dots/m2
	Pixel configuration
	1R1G1B
	Package mode
	SMD2727
	Pixel resolution
	64dots(W)*32dots(H)
LED Cabinet	Max Power
	25W
	Module thickness
	22mm
	Weight
	0.37kg
	Drive type
	Constant drive
	Scan mode
	1/8
	Port type
	HUB75-A
	Brightness of white balance
	≥5500 6000cd/m2
Power	Dimension
	960mm*960mm*100 mm
	Monomer Module Number
	36pcs
	Power supply
	5V/40A*6pcs
	Thermal discharge
	fan 2pcs
	Pixel per cabinet
	96mm*96mm
Control system	Best viewing distance
	5M 15M
	Best viewing angle
	120°(W) 110°(H)
	Temperature
Main technical parameter	storage:-35°C +85°C working:-20°C +50°C
	Relative humidity
	10%-95%
	Thickness
	122mm
	Working voltage
	AC220V±10%
Power	Average Power consumption
	350W/
	Max Power consumption
	≤1200W/
Control system	Current
	≤20mA(single LED)
	CPU
Main technical parameter	Pentium4 or above P4
	Operation system
	WIN98/2000/NT/XP/WIN7
Main technical parameter	Control method
	Synchronization
	Driving device
	Constant drive IC
	Refresh frequency
	≥1920HZ
	Grey scale/colors
Main technical parameter	4096gray level/16.7M colors
	MTBF
	≥10000hours
	Power switch
Main technical parameter	Automatic switch
	Display Mode
	≥800*600/1024*768

Features:

- 1.Outdoor high resolution 27,777 pixels per square meter for high image quality.
- 2,Suit for strict weather conditions with IP65 rating.
- 3,Seamless splicing.
- 4, Energy saving: low electric current, high-bright.
- 5, Super high brightness 6000nits makes led screen still be very clear under the sunshine.
- 6,.Scientific structure design and cooling system ensures the stability and reliability, even long time continuous use.

Project Show:



SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District,
Shenzhen