Indoor LED Video Wall Seamless Easy Installation

Basic Information

. Place of Origin: China Brand Name: Sol-colur

CE/FCC/ROHS/ISO · Certification: P1.25/P1.5/P1.8/P2 Model Number:

• Minimum Order Quantity: 1pcs

• Price: Negotiated

· Packaging Details: Carton box, Wooden case

• Delivery Time: 10 working days after receiving deposit

Payment Terms: L/C, T/T

. Supply Ability: 5000sqm/month



Product Specification

Module Size: 320x160mm Cabinet Size: 640x480mm

 Cabinet Material: Die Casting Aluminum

Cabinet Weight: 4.2kg

LEDs Brand: Nationstar/Kinglight/Ruisheng/Mulinsen/Speci

• Refresh Rate: 3840Hz-7680Hz 14bit - 16bit Gray Level: Brightness: 450-500cd/ • Maintenance: Front • Environment: Indoor Max. Power Consumption: 390W/ Ave. Power Consumption: 130W/

. Operating Voltage: AC 110V /220V ± 10%

• Highlight: 640x480mm Indoor LED Video Wall,

Easy Installation Indoor LED Video Wall,



More Images



640x480mm Indoor Seamless Easy Installation LED Video Wall Display Screen Product features:

- 1. Die-cast aluminum cabinet design, ultra-light and ultra-thin.
- 2. High-precision intelligent module, seamless splicing of the large screen.
- 3. Ultra-high contrast, high definition (support HDR high dynamic display effect).
- 4. Wide range of applications, such as control rooms, monitoring rooms, high-end commercial displays, studios, etc.

Product technical specifications:

Parameter				
Model	P1.25	P1.5	P1.8	P2
Pixel pitch	1.25mm	1.5mm	1.8mm	2mm
LEDs	SMD1010	SMD1212	SMD1515	SMD1515
Cabinet size	640x480x48nn			
Cabinet material	Die Casting Aluminum			
Cabinet weight	4.2kg			
Maintenance methods	Front			
Module size	320x160mm			
Module resolution	256x128 dots	208x104 dots	172x86 dots	160x80 dots
Screen resolution	64000 dots/	422500 dots/	288906 dots/	250000 dots/
Brightness	≥450 cd/	≥450 cd/	≥450 cd/	≥500 cd/
Viewing angle	150°/130°			
Max. power consumption	390W/	390W/	390W/	390W/
Ave. power consumption	130W/	130W/	130W/	130W/
Refresh rate	3840Hz-7680Hz	3840Hz-7680Hz	3840Hz-7680Hz	3840Hz-7680Hz
Gray level	14bits-16bits	14bits-16bits	14bits-16bits	14bits-16bits

Reference pictures:



SOL COLOTUR SHENZHEN SOL COLUR DISPLAY CO.,LTD

+86 13751136904

chenhao@sol-colour.com

sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen