CE/FCC/ROHS/ISO · Certification:

P2.5 Model Number: Minimum Order Quantity: 1pcs • Price: Negotiated Packaging Details: Wooden case

• Delivery Time: 10 working days after receiving deposit

• Payment Terms: L/C, T/T

5000sqm/month . Supply Ability:



Product Specification

• Highlight: LED Poster Display 640x1920mm, Movable Splicable LED Poster Display,

640x1920mm LED Poster Screen



Product Description

Movable and Splicable LED Poster Dispaly Screen 640x1920mm

Product features:

- 1. Slim & Lightweight Design, Little Space to Install.
- 2. Adjustable Back Bracket.
- 3. Smart Cloud Management.
- 4. Multi-installation Method.

Product technical specifications:

Item	Parameter
Model	P2.5
Pixel pitch	2.5mm
Screen area	640x1920mm
Resolution	256x768 dots
Brightness	600-800nits
Viewing angle	140°/140°
Viewing Distance	≥2m
Refresh rate	3840Hz - 7680Hz
Gray level	14bits - 16bits
Max power consumption	720W/
Average power consumption	220W/
Maintenance method	Rear/Front
IP level	IP30
Communications	Wifi/LAN/USB drive

SOL COLOTUR SHENZHEN SOL COLUR DISPLAY CO.,LTD



+86 13751136904



chenhao@sol-colour.com



sol-colur.com

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen