

P1.5 Flexible LED Display Screen Cylindrical LED Screen With Silicone Soft

Basic Information

. Place of Origin: China Brand Name: Sol-colur

CE/FCC/ROHS/ISO · Certification:

P1.5 Model Number: • Minimum Order Quantity: 1sqm • Price: Negotiated

· Packaging Details: Flight case, Wooden case

• Delivery Time: 10 working days after receiving deposit

Payment Terms: L/C, T/T

. Supply Ability: 5000sqm/month



Product Specification

LEDs Brand: Nationstar/Kinglight/Ruisheng/Mulinsen/speci

Refresh Rate: 3840Hz-7680Hz


IP30 Protection Level: Max. Power Consumption: ≤390w/m² Ave. Power Consumption: ≤130w/m² 16.7M . Color Value: 150°/130° Viewing Angle: Module Size: 320mmx160mm

· Uasge: Indoor

Working Voltage: AC100~240 50/60Hz 100,000 Hours Lifespan:

· Highlight: P1.5 Flexible LED Display Screen,

P1.5 Cylindrical LED Screen, Soft Frame Cylindrical LED Screen



More Images



P1.5 Cylindrical Screen Flexible LED Display Panel with Silicone Soft Frame and PCB Board Product features:

- 1. Standardized size: 320mmx160mm
- 2. High reliability, high contrast
- 3. Strong magnetic adsorption design, good flatness
- 4. Easy to bend, convenient and seamless splicing
- 5. Various shapes: inner arc, outer arc, cylindrical, wavy, etc.

Product technical specifications:

1	
Item	Specification
Model	P1.5
Pitch	1.538mm
LEDs	SMD1212
Module size	320mm x160mm
Module resolution	204x102
Pixel density	422500 dot/m ²
White balance brightness	>450 cd/m²
viewing angle	150°/130°
(Horizontal/Vertical)	150°/130°
Viewing distance	>1.5m
Color value	16.7M
Max. power consumption	390w/m²
Ave. power consumption	130w/m²
Refresh rate	3840Hz
Application Scenario	Indoor(IP30)
Working voltage	AC100~240 50/60Hz
Lifespan	100,000 Hours

Reference pictures:





SOL COL TURN SHENZHEN SOL COLUR DISPLAY CO.,LTD

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen