Cylindrical Flexible Led Display Panels P2mm

Basic Information

. Place of Origin: China . Brand Name: Sol-colur

CE/FCC/ROHS/ISO · Certification:

P2 Model Number: • Minimum Order Quantity: 1sqm • Price: Negotiated

· Packaging Details: Flight case, Wooden case

• Delivery Time: 10 working days after receiving deposit

Payment Terms: L/C, T/T

. Supply Ability: 5000sqm/month



Product Specification

LEDs Brand: Nationstar/Kinglight/Ruisheng/Mulinsen/speci

Refresh Rate: 3840Hz-7680Hz

IP30 Protection Level: Max. Power Consumption: ≤450w/m² Ave. Power Consumption: ≤150w/m² • Color Value: 16.7M 150°/130° Viewing Angle: Module Size: 320mmx160mm

· Uasge: Indoor

Working Voltage: AC100~240 50/60Hz 100,000 Hours Lifespan:

· Highlight: Flexible Led Display Panels P2mm,

> Cylindrical Led Display P2mm, Cylindrical P2 LED Display



P2 Cylindrical Screen Flexible LED Display Panel with Silicone Soft Frame and PCB Board

Product features:

- 1. Standardized size: 320mmx160mm
- 2. High reliability, high contrast
- 3. Strong magnetic adsorption design, good flatness
- 4. Easy to bend, convenient and seamless splicing
- 5. Various shapes: inner arc, outer arc, cylindrical, wavy, etc.

Product technical specifications:

Item	Specification
Model	P2
Pitch	2mm
LEDs	SMD2020
Module size	320mm x160mm
Module resolution	160x80
Pixel density	250000 dot/m ²
White balance brightness	500-800 cd/m ²
viewing angle	150°/130°
(Horizontal/Vertical)	150°/130°
Viewing distance	>2m
Color value	16.7M
Max. power consumption	450w/m²
Ave. power consumption	150w/m²
Refresh rate	3840Hz
Application Scenario	Indoor(IP30)
Working voltage	AC100~240 50/60Hz
Lifespan	100,000 Hours

Reference pictures:





SOL COL TURN SHENZHEN SOL COLUR DISPLAY CO.,LTD

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen