



## Sticky Module Transparent Led Film Display Ultra Thin Flexible Led Screen 1000x240mm

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Sol-colur
- Certification: CE/FCC/ROHS/ISO
- Model Number: P4-8/P6/P8/P10/P16/P20/P30
- Minimum Order Quantity: 1pcs
- Price: Negotiated
- Packaging Details: Carton box, Wooden case
- Delivery Time: 10 working days after receiving deposit
- Payment Terms: L/C, T/T
- Supply Ability: 5000sqm/month



### Product Specification

- Module Size: 1000x240mm
- Brightness: 1200nits-3500nits
- Transparency: 90%-95%
- Refresh Rate: 3840Hz-7680Hz
- Max. Power Consumption: 720W/
- Ave. Power Consumption: 260W/
- Gray Level: 16bits
- Viewing Angle: 160°
- Scan Mode: Static Scan
- Operating Voltage: AC 110V/220V ±10%, 50-60Hz
- Highlight: **Sticky Module Led Film Display ,  
Led Film Display 1000x240mm ,  
Ultra Thin Flexible Led Screen 1000x240mm**

for more products please visit us on [sol-colur.com](http://sol-colur.com)

## Product Description

### Ultra-thin Sticky Module Film LED Screen Install Directly on Glass 1000x240mm

#### Product features:

1. It is easy to install, no steel structure is required, and it can be installed directly with glass.
2. High transparency, high durability, UV resistance, high and low temperature resistance.
3. Low power consumption design, energy-saving and environmentally friendly, in line with the concept of green and low-carbon development.
4. Ultra-wide viewing angles 160°
5. A wide range of applications.

#### Product technical specifications:

Parameter							
Model	P4-8	P6	P8	P10	P16	P20	P30
Module size	1000x240mm						
Module resolution	250x30 dots	166x40 dots	125x30 dots	100x24 dots	64x15 dots	50x12 dots	34x8 dots
Screen resolution	250x125 dots	166x166 dots	125x125 dots	100x100 dots	64x64 dots	50x50 dots	34x34 dots
Brightness	2500 cd/	3500 cd/	3500 cd/	3500 cd/	2500 cd/	2000 cd/	1200 cd/
Refresh rate	3840Hz-7680Hz	3840Hz-7680Hz	3840Hz-7680Hz	3840Hz-7680Hz	3840Hz-7680Hz	3840Hz-7680Hz	3840Hz-7680Hz
Gray level	16bits	16bits	16bits	16bits	16bits	16bits	16bits
Scan mode	Static scan	Static scan	Static scan	Static scan	Static scan	Static scan	Static scan
Viewing angle	160°						
Transparency	90%	93%					95%
Max. power consumption	720W/	720W/	720W/	720W/	720W/	720W/	720W/
Ave. power consumption	260W/	260W/	260W/	260W/	230W/	220W/	200W/
Operating temperature	-0-55℃						
Operating humidity	10-75% RH						
Operating voltage	AC 110V / 220V ±10%						

**SOL COLUR SHENZHEN SOL COLUR DISPLAY CO.,LTD**

+86 13751136904

[chenhao@sol-colour.com](mailto:chenhao@sol-colour.com)

[sol-colour.com](http://sol-colour.com)

2nd Floor, Building 8, Nangang Third Industrial Zone, TangtouCommunity, Shiyan Street, Bao'an District, Shenzhen